

SUMMARY



Image is for illustrative purpose only

Wires

Low	36
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Download

[Request a quote](#)

[Catalog](#)

Series	1R
Termination type	Female crimp
IP rating	50
Cable Ø	0.00 - 0.00 mm
Matching parts	FGG.1R.336.GLC92
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	EGG*: Fixed receptacle, key (G) or key (A)
Keying	
Housing Material	Crastin® PBT, gray
Cable Fixing	∅ 0 - 0 mm
Variant	

Performance

Configuration	1R.336 : 36 low voltage
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)
Rated Current	2.5 Amps

Specifications


Contact Type: Crimp
Test voltage (kV rms) Contact-contact: 1.5

Others

IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	B	C	E	G	L
mm.	24.5	10.5	34.5	3.2	2.2	31.5
in.	0,96	0,41	1,36	0,13	0,09	1,24

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.701.V

Crimp settings: AWG/Selector = 22-24-26/6-5-5

Positionner: DCE.91.070.BVM

Extractor: DCF.91.070.2LT

Replacement contact: EGG.0B.655.ZZM

Cables