

## Datasheet for part number CA02COME18-10SB01

Our Catalog Part Number: CA02COM-E18-10S-B-01

Our Global Manufacturing Part Number: 121518-0013

Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA COM-B

| Product Datasheet                             |  |
|---|--|
| Bayonet                                       | Connector with Bayonet Coupling  |
| Shell Style                                   | Box mounting receptacle  |
| Gender  | Socket   |
| Shell Size                                    | 18   |
| Contact Arrangement                           | 18-10  |
| Number of contacts                            | 4 contacts size 12   |
| Contact Type                                  | Metric Crimp   |
| Contact Plating                               | Hard silver  |
| Contacts installed                            | not assembled, packed separately   |
| Contact Rating at +20 °C (68 °F) (Size 25/12) | 41 A   |
| Contact Resistance (Size 25/12)               | 3 mΩ   |
| Operating Voltage                             | In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.                     |
| Insulator Resistance                          | ≥1000 MΩ   |
| Test Voltage                                  | 1600 Vrms  |
| Air and Creepage Paths (Min)                  | 1,1 mm   |
| Ambient Temperature                           | Standard insulator material -55°/+125°C (-67/257°F)  |
| Safety Provisions                             | IP67 (only applies if a grommet is used)   |
| Mating Cycles                                 | 500 min  |
| Sep. Force per Contact (Size 25/12)           | 1,5 N  |
| Gauge   | For infos on Gauge please see catalog VG95234, part 1  |
| Coupling Torque                               | Closing: 4 Nm max / Opening: 0,58 Nm min   |
| Contact Retention (Size 25/12)                | 55 N   |
| Shell Material                                | Aluminium alloy  |
| Shell Plating                                 | Nickel plated  |
| Insulator and Gromet Material                 | CR-Elastomere  |
| Contact Material                              | Copper alloy   |
| Harnessing Info: Contact Cross-Section        | See assembly instruction   |
| Harnessing Info: Insulator Diameter           | See assembly instruction   |
| Wire Stripping (Size 25/12)                   | 6,2 mm   |
| General Info                                  | All tests in accordance with VG95319 and/or if applicable with VG95210 except salt spray resistance and heat and humidity endurance test |