

APPLICATOR PARTS LIST

TYPE

HINGEBAR MARK III

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER	1	692900-1	42	FRONT STAB BAR	1	811006-1	
2	INS. CRIMPER			43				
3	ANVIL	1	843101-1	44	HINGE BLOCK AND STAB	1	810974-1	
4	ANVIL INSET INSET	1	456878-1	45	HINGE PIN	1	811007-1	
5	SHEAR BLADE	1	810412	46	GUARD, FRONT STAB	1	810412-1	
6	REAR SHEAR PLATE	1	456889-1	47	HINGEBAR ASS'Y	1	565062-1	
7	SHEAR BLADE SPRING SPRING	1	810410-1	48	HINGEBAR SPRING	2	3-23846-5	
8	FRONT SHEAR PLATE	1	388632-5	49	STRIP GUIDE STOP	2	810417	
9	REAR ANVIL SPACER PLT.			50	STRIP HOLD DOWN	1	810411	
10	FRONT ANVIL SPACER PLT.			51	SPACER, COMP. SPRING	2	811070-1	
11	TOOL SPACER			52	CAM FOLLOWER HOLDER	1	810409	
12	CRIMP SPACER			53	CAM FOLLOWER	1	24746-1	
13	FRONT STRIP GUIDE	1	811052-6	54	SPRING BRACKET	1	810418	
14	REAR STRIP GUIDE	1	388621-1	55	CAM FOLLOWER SPRING	1	810408	
15	RAM	1	473828	56	HOOK HOLDER	1	810419	
16	RAM RET. PLT. RAM RET. PLT.	1	465004-2	57	SHEAR PICK-UP HOOK	1	810416	
17	ADJ. PLT ADJ. PLT	1	811010-1	58	HOLD DOWN, HINGEBAR	1	811009-1	
18	PROTECTIVE PLUG PROTECTIVE PLUG	1	23141-1	59	DEPRESSOR SCREW	1	810642-1	
19	APPLICATOR MOUNT ASSY.			60	WASHER	2	376482	
20	BASE PLATE	1	465238-1	61	FEED FINGER SPRING	1	810421-1	
21	BASE BLOCK			62	DOWEL PIN	2	1-21030-5	
22	STRIP GUIDE PLATE			63	MICRO SWITCH	1	23496-1	
23	ANVIL HOLDER	1	810423	64	MICRO SWITCH COVER	1	22689-2	
24	AUX. ANVIL HOLDER			65	BRACKET, MICRO SW.	1	811074-1	
25	STRIPPER			66	CONNECTOR	1	22787-2	
26	STRIPPER MOUNT			67	HOOK HOLDER SCREW	1	810413	
27	RETAINER PLATE			68				
28	STRIPPER MOUNT BRACKET			69	SPACER (ANVIL HOLDER)	1	811223-1	
29	STRIPPER BUSHING			70	LEAD WIRE	1	465918-1	
30	STOCK DRAG	1	811063-2	71	DOWEL PIN	1	465702-1	
31	STOCK DRAG HANDLE			72				
32	STOCK DRAG STUD			REV.	REVISION RECORD	DATE	BY	ECN
33	STOCK DRAG SPRING	2	810135	A	GUARD WAS 465050	1/6/72	JW	L9328
34	STOCK DRAG ADJ. SCREW			B	REV. PER ECN	1-6-76	JW	R1491
35	FEED FINGER HOLDER	1	810131	B1	ADD 62056-6	3-9-77	JW	R1998
36	FEED FINGER	1	810422	C	REV. PER ECN	4-29-77	JW	R2013
37	FEED FINGER TIP	1	810420	D	REV. PER ECN	10-18-78	JW	R12716
38	FEED FINGER STUD STUD	1	810414-1	E	REV. PER ECN	1-8-79	JW	R2839
39	BASE CASTING	1	570238	F	REV PER ECN RS191	6-27-83	JW	-
40	GUARD, ASS'Y	1	457698-4	G	ECN R 7674	10-28-83	JW	-
41	INSET, GUARD	1	810654	H	REV; ECN A-105788	7-88	MD	-
				J	ECN A-830891	8-91	JW	-

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL		62056-1 62056-3 62056-6
WIRE SIZE	CRIMP HEIGHT	
18	.052	
16	.056	
14	.062	
12	.072	
CRIMP WIRE	SIZE	TYPE
	.160	TL
INSUL.		
SLEEVED		
INSULATION RANGE		WIRE RANGE
		18-12
EXPLODED VIEW		
A-6004-3		A-6004-4
REMARKS:		
RIGHT HAND		
END WIRE APPLKATOR FOR TERMINAL 62056 PRIOR TO REV W USE ANVIL PIN 692901-1		
RECOMMENDED SPARE PARTS		
THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC 1-471273-3		
SERIAL NO.	DATE SHIPPED	DESIGNED
		MK 5-17-72
CUSTOMER NAME AND ADDRESS		CHK'D.
		1EM 5-17-72
APPLICATOR NUMBER		APP'D.
REV J	566092-1	SHEET 1 of 1