APPLICAB	LE STAND	ARD									
OPERATING			FE 00 TO 05 00 (1)		- 1	STORAGE			-10 °C TO 60 °C ©		
RATING	TEMPERATURE RANGE		-55 °C TO 85 °C (1)		OPERATING				40 % TO 80 %		
	VOLTAGE CURRENT				RAN STO	GE RAGE HI	JMIDITY				
			0.4 A RAN			IGE 40			40 % TO 70 %	% TO 70 % ^②	
			SPECIFICATIONS								
ITEM		TEST METHOD				REQUIREMENTS					AT
CONSTRU	CTION										
	CAMINATION		LY AND BY MEASURING II	NSTRUM	ENT.	ACCO	RDING T	TO DR	AWING.	×	×
MARKING			MED VISUALLY.							×	×
	CHARACT	ERISTI	CS								
CONTACT RESISTANCE		,				45 mΩ MAX.					
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				55 mΩ MAX.					_
INSULATION BESISTANCE		250 V DC				100 MΩ MIN.					-
RESISTANCE VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLA	ASHOVI	FR OF	R BREAKDOWN.	×	+-
MECHANICAL CHAR							.0,1001	01.		^	
MECHANICA			S INSERTIONS AND EXTR	ACTION	IS.	A CO	NTACT	DESIS	STANCE: 55 mO MAY	×	Τ_
OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					
VIBRATION		FREQUENCY 10 TO 55 Hz,				① NO ELECTRICAL DISCONTINUITY OF				×	-
		AMPLITUDE: 1.5 mm,				1 μs.					
SHOCK		AT 2h FOR 3 DIRECTIONS.				+			STANCE: 55 mΩ MAX.	×	+
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				^	
ENVIRONI	MENTAL CI		TERISTICS	110110.			. ,				
DAMP HEAT	VILIVIAL OI		DAT 40±2°C, 90 ~ 95	5 % 96	h	A CO	NTACT	RESIS	STANCE: 55 mΩ MAX.	×	Τ_
(STEADY STATE)		EXPOSED AT 40 ±2 °C, 90 ° 93 %, 90 H.				② INSULATION RESISTANCE:100 MΩ MIN.					
RAPID CHANGE OF		TEMPERATURE-55→+15~+35→ +85→+15~+35°C				-			RACK AND LOOSENESS	×	T-
TEMPERATURE		TIME $30 \rightarrow 2 \sim 3 \rightarrow 30 \rightarrow 2 \sim 3$ min UNDER 5 CYCLES.					PARTS.				
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 55 mΩ MAX. ② NO HEAVY CORROSION.				×	_
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA 38)								×	-
RESISTANCE TO		,				NO DEFORMATION OF CASE OF					-
SOLDERING HEAT		: 220 °C MIN,				EXCESSIVE LOOSENESS OF THE					
		FOR 60 s 2) SOLDERING IRONS : 360 °C.				TERMINALS.					-
		2) SOLDE	,	5 6						×	_
SOLDERABILITY		FOR 5 s SOLDERED AT SOLDER TEMPERATURE,				A NEW UNIFORM COATING OF SOLDER					+-
		240 ± 3 °C, FOR IMMERSION DURATION, 3 s.				SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.					
COUNT	r ne	SCRIPTION	ON OF REVISIONS		DESIG	NED.			CHECKED	D4	ATE
A 22011		JESIC DESIGNATION			STEEL						
	TEMPERATUR	E RISE INCLUDED WHEN ENERGIZED. INDICATES A LONG-TERM STORAGE STATE				APPROVED HS.OKAWA				06.10.23	
(2)						CHECKED			HS.OZAWA	06.10.20	
	FOR THE UNU:	SED PROD	ED PRODUCT BEFORE THE BOARD MOUNTED.						KY.NAKAMURA		
Unless otherwise specified,			d. refer to JIS C 5402.						AK.SUZUKAWA		
•						DRAWN DRAWN					
		t AT:Assurance Test X:Applicable Test			PART	RAWING NO.			ELC4-150567-21 FX8-120P-SV (91)		
HS	SPECIFICATION SHEET HIROSE ELECTRIC CO., LTD.									<u> </u>	1/1
	וחותי	COSE ELECTRIC CO., LTD.			CODE	= NO.	U	LJ/C	>-UUUU-U-91 2	′U \	[17 T