	I G	т п		D	0	D. D	A		_
4	X Thread								4
ယ					LAYOUT	SHOWN AS EXAMPLE			3
		Keying Shown as example							
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal							
	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum					Country FR	Jurisdiction & Control List Not Listed		2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories				PN: 8D113W98AA				
	-Temperature Range <sub>:</sub> -65°C to +175°C -Salt Spray : 500 hours			A 27-09-2016 First Release					
				ISS DATE Designed By:	Latest modification - by Date:	,	CUSTOMER DRAWING	MOD N°	
				TITLE	Δ	luminium Inlin	e plug 8D series		
_	BASIC SERIES: 8D 1 - 13 W	98 A A		SCALE		neral linear olerances: ±	NPRDS / PROJECT <b>859</b>		
_	SHELL TYPE : In line Receptacle         CONTACT TYPE : Standard Crimp Contact         SHELL SIZE : 13         PLATING : W = Olive drab Cadmium         CONTACT LAYOUT : 13-98				SOURIAU       This document is the pr         SOURIAU       SOURIAU         it must not be reprodu				
					communicate		communicated without pe		
				A3		D113W98AA		1/2	
	H G	FE		D	C	В	A		

ſ	Т	G	П	п		C	σ	A		
		Contact Layout								
4		(Insert arrangement 13-98)							4	
		X-axis (mm)         Y-axis (mm)           A         +.000 (0.00)         +.195 (4.95)           B         +.125 (3.18)         +.150 (3.81)           C         +.193 (4.90)         +.030 (0.76)           D         +.104 (4.17)        105 (2.07)           E         +.000 (0.00)        135 (3.43)           F        164 (4.17)        105 (2.67)           G        193 (4.90)         +.030 (0.76)           H        125 (3.18)         +.150 (3.81)           J         +.065 (1.65)        015 (0.38)           K        065 (1.65)        015 (0.38)								
ى ع	Shell size Arrangement no.	Number of contacts         Size contacts         Service rating         Contact location         Supers           10         20         I         All         MS200							3	
	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						vith ird party			
N						Countr		& Control List Listed	2	
						PN: 8D113W98AA				
		27-09-2016 First Release								
_					ISS DATE			MOD	) N°	
					Designed By:	Date:	CUST	TOMER DRAWING		
					TITLE	Aluminium	n Inline plug 8D	series		
_					SCALE NA	General linear Tolerances:		PRDS / PROJECT <b>859</b>	1	
					SOURIA	WWW.SOURIAU.C	OM	This document is the property of SOURIAU it must not be reproduced or ommunicated without permission		
					FORMAT	SOURIAU		SHE		
L		I	Γ		A3	8D113W		2/	2	
	Н	G	l F	E	D	C	В	A A		