[T Q T M		0	₩ 2	>]
4						4
ω			LAYOUT SHOWN AS EXA	MPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III ØS 21.8 Max					
	Image: Naterial Image: Aluminium Z 31 Max Source of the Products which does not comply with due to a use of the Products which does not comply with sulator : Thermoplastic the Specifications issued by either of the Parties or by a third party ontacts : Copper Alloy					
N	-Contact Plating : Gold over copper Alloy 0.8µm minimum		CountryJurisdiction & Control ListFRNot Listed			2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D509W98SC			
	-Temperature Range - 65°C to +175°C	A 15-10-2016	5 First Release			
	-Salt Spray : 500 hours	ISS DATE	Latest modification - by		MOD N°	_
	-Mass : 12.77 g ± 10%	Designed By:	Date:	CUSTOMER DRAWING		T
		TITLE	Aluminium Plug 8D series			
_	BASIC SERIES: 8D 5 - 09 W 98 S C SHELL TYPE : Plug with RFI Shielding - 09 W 98 S C	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION	- SUURIAU	SOURIAU WWW.SOURIAU.COM This document is the prop SOURIAU it must not be reproduc communicated without new			_ `
	SHELL SIZE : 09 CONTACT TYPE : SOCKET(500 Matings)		FORMAT SOURIAU DRG N° s			_
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 05	A3			SHEET	
		/\3	8D509W9	036-6	1/2	

r		۵	г т	m		0
		Contact Layout				
4	-X	$ \begin{array}{c} $				
	Shell Arrangement Numb size no. 9 -98 3	+.065 (1.65) +.038 (0.97) +.000 (0.00)075 (1.91) 065 (1.65) +.038 (0.97) 065 (1.65) +.038 (0.97) 				
ω						
	\vdash					SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either o
N						(professional recommenda Count FR PN: 8D509
					A 15-10-20 ISS DATE Designed By:	16 First Release
<u> </u>					TITLE SCALE NA	Alumi General linear Tolerances: ±
					FORMAT A3	SOURIAL 8D509V
	Н	G	F	E	D	C

