



# PC 5/ 8-G-7,62 BK - 1708291

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB headers, nominal current: 41 A, number of positions: 8, pitch: 7.62 mm, color: black, contact surface: Tin, mounting: Wave soldering



## Key Commercial Data

Packing unit	50 STK
GTIN	 4 046356 995429
GTIN	4046356995429

## Technical data

### Dimensions

Pitch	7.62 mm
Dimension a	53.34 mm
Constructional height	14.29 mm
Length of the solder pin	5 mm

### General

Range of articles	PC 5/..-G
Rated voltage (III/3)	630 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	41 A
Color	black
Number of positions	8

### Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

### Approvals

# PC 5/ 8-G-7,62 BK - 1708291

## Approvals

Approvals

EAC / cULus Recognized


---

Ex Approvals

---

## Approval details

EAC		B.01742
-----	---	---------

cULus Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E60425-19920722
	D	B	C
Nominal voltage UN	600 V	300 V	150 V
Nominal current IN	5 A	41 A	41 A

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>