

Datasheet for part number CA3106E22-14SB15F0

	Our Catalog Part Number: CA3106E22-14S-B-15-F0		
Our Global Manufacturing Part Number: 121575-3208			
	Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA BAYONET		

Connector with bayonet coupling Plug, straight Shielded connector with endbell for shielded braids and heat shrinkable boots
Shielded connector with endbell for shielded braids and heat shrinkable boots
and heat shrinkable boots
Socket
22
22-14
19 contacts size 16
AWG Crimp
Hard silver
no, delivery without contacts
yes
22 A
6 mΩ
AWG 18/16
In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.
Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 M Ω
2000 Vrms
1,1 mm
Standard insulator material -55°/+125°C (-67/257°F)
IP67 acc. to DIN 40 050 and IP68 (1 bar pressure for 16h)
500 hours salt spray resistant
500 min
1,0 N
For infos on Gauge please see catalog VG95234, part 1
Closing: 11 Nm max / Opening: 0,8 Nm min
35 N
Aluminium alloy
Olive drab chromate over cadmium plating (conductive)
CR-Elastomere
Copper alloy
See assembly instruction
See assembly instruction
6,2 mm

Specifications and dimensions subject to change.



Datasheet for part number CA3106E22-14SB15F0

	Our Catalog Part Number: CA3106E22-14S-B-15-F0	
Our Global Manufacturing Part Number: 121575-3208		
	Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA BAYONET	

Product Datasheet	
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210