


This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.



L17D TZK **K FM (**=09,15,25,37)

Part Number	A	B
L17D TZK 09K FM	21 (.827")	38.3 (1.508")
L17D TZK 15K FM	39.5 (1.555")	40.5 (1.594")
L17D TZK 25K FM	54.4 (2.144")	47.3 (1.862")
L17D TZK 37K FM	70.9 (2.791")	52.2 (2.055")



REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
A			5/29/07	

D-SUB TECHNICAL DATA

Material and finish: die-cast,nickel plated or black iron zinc

Cable strain relief: Steel fibre reinforced Polycarbonate (UL94R-0)for ENI/RFI screening

Locking screws: Long solid jackscrew with full metal for indication of thread

Temperatrue range: -40°C to 120°C

Cable diameter: 4.0-13.0mm

Attenuation factor: >40 dB between 30 MHz and 1 GHz

Meet requirements: VDE 0971, FCC 20780, 89/336/EU

PRODUCT CODE

L 17DTZK **K FM

RoHS Compliance

Series 17DTZK:90°

Position:9,15,25,37

Screwlock Full Metal

Bulk Package

UNLESS OTHERWISE SPECIFIED TOLERANCES	APPROVAL		DATE
U.S. METRIC	DRAWN	Issa.peng	5/29/07
.X +/- 0.4	CHECKED	tk.wang	5/28/07
.XX +/- 0.30	CHECKED		
.XXX +/- 0.20			
FRACTIONS +/-			
ANGLES +/- 2°			
FOR MATERIALS AND FINISHES SEE NOTES	DRAWING FILE : PE master/drawing/Dsub		
REMOVE SHARP EDGES	ANGLE OF PROJECTION		
DIMENSIONS			
U.S. INCHES			
METRIC MM			

Amphenol

TITLE		SIZE	DRAWING NO.	REV.
METAL HOOD		A4	L17D TZK **K FM	A
SCALE	NONE	SHEET 1 OF 1		