

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AJ	17	B	REV PER EC 0S14-0092-05	10DEC2005	REH KW

INSULATING DISK

CONNECTOR SUB-ASSY

COAXIAL CABLE

305±5

1064474-1  
PART NUMBER

<b>ELECTRICAL</b>	
FREQUENCY	DC - 6 GHz
NOMINAL IMPEDENCE	50 OHMS
VOLTAGE RATING	250 VOLTS (VRMS MAX) @ SEA LEVEL
VSWR (MATED CONNECTORS ONLY)	1.20:1 MAX @ 2 GHz 1.40:1 MAX @ 6 GHz
INSULATION RESISTANCE	1,000 MEGOHMS MIN
DIELECTRIC WITHSTANDING VOLTAGE	500 VOLTS (VRMS MIN) @ SEA LEVEL
<b>MECHANICAL</b>	
CONNECTOR DURABILITY	100 MATING CYCLES
<b>ENVIRONMENTAL</b>	
TEMPERATURE RATING	-40°C(-40°F) TO +125°C(257°F)

CONNECTOR	MATERIAL	FINISH
OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE
CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE
DIELECTRIC	POLYPROPYLENE, GF	N/A
CABLE		
JACKET	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A
SHIELD	SILVER PLATED COPPER WIRE, 38 AWG	N/A
DIELECTRIC	PERFLUOROALKOXY (PFA) OR POLYTETRAFLUOROETHYLENE (PTFE)	N/A
CENTER CONDUCTOR	SILVER PLATED COPPER CLAD STEEL, 30 AWG	N/A
INSULATING DISK	POLYESTER	N/A
COMPONENT	MATERIAL	FINISH

PRODUCT SPEC

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	BB	10/9/92	Tyco Electronics Corporation Harrisburg, PA 17105-3608			
DIMENSIONS: mm		CHK						
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	ADowns	10/12/92	NAME OSMT RIGHT ANGLE JACK PIGTAIL ASSY, HIGH TEMP			
0 PLC ± -		PRODUCT SPEC						
1 PLC ± -		APPLICATION SPEC			SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
2 PLC ± -					A2	00779	C=1064474	-
3 PLC ± -		WEIGHT	-		SCALE		SHEET	REV
4 PLC ± -					12:1		1 of 1	B
ANGLES ± -		CUSTOMER DRAWING						
FINISH								

AMP 1471-9 REV 31MAR2000

1064474

B

A