



RECOMMENDED MOUNTING HOLE PATTERN FOR 1.57 THICK P.C. BOARD

- PINS TO COMPLY WITH AMP SOLDERABILITY SPEC. 109-11-3.
- 0.00381 MIN MATTE TIN LEAD PLATE OVER 0.00127 MIN NICKEL.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED PLATE AREA, 0.00381 MATTE TIN LEAD IN THE LOCALIZED PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.
- 0.00381 MIN MATTE TIN PLATE OVER 0.00127 MIN NICKEL.
- 0.00076 MIN GOLD PLATE IN THE LOCALIZED PLATE AREA, 0.00381 MATTE TIN IN THE LOCALIZED PLATE AREA, BOTH OVER 0.00127 MIN NICKEL.

OBSOLETE	BRASS, GOLD	NYLON, 94V-0, WHITE	1-794066-1
	BRASS, TIN	NYLON, 94V-0, WHITE	1-794066-0
	BRASS, GOLD	NYLON, 94V-0, WHITE	-794066-2-
	BRASS, TIN LEAD	NYLON, 94V-0, WHITE	-794066-1-
PIN CONTACT MATERIAL AND FINISH		HOUSING MATERIAL AND COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN K WHITAKER 6-12-95	CHK R SWING 6-12-95	APVD R ORSTAD 6-13-95	NAME
0 PLC ± -	1 PLC ± -				TE Connectivity
2 PLC ± 0.13	3 PLC ± -				HEADER ASSEMBLY, 12 CIRCUIT, DOUBLE ROW VERTICAL, MINI-UNIVERSAL MATE-N-LOK
4 PLC ± -	ANGLES ± -				SIZE: A1
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SCALE: 8:1	SHEET 1 OF 1	REV D1

CUSTOMER DRAWING