


Capacitor, aluminum, 47 uF, +/-20% Tol, 16VDC@85° C



Dimensions (mm)		
Symbol	Dimension	Tolerance
D	6.3	+/-0.5
L	5.4	+0.25/-0.1
A	6.6	+/-0.2
B	6.6	+/-0.2
C	7.8	MAX
W	0.65	+/-0.1
E	2.6	+/-0.2
P	1.8	+/-0.2
F	0.3	MAX

Packaging Specifications	
Package Kind:	T&R
Package Size:	380mm
Package Quantity:	1000

General Information	
Supplier:	KEMET
Part Type Description:	Surface Mount Aluminum Electrolytic
Style:	Surface Mount Vertical Can
Lead Type:	V-Chip

Specifications	
Capacitance:	47 uF
Voltage @ rated temp:	16VDC
Rated Temperature:	85° C
Tolerance:	+/-20%
VDC Surge:	20VDC
Life @ rated temp:	2000 Hrs
RoHS:	Yes
Hi Temp Solder:	Yes
Temperature Range:	-40/+85C
Leakage Current:	8 uA
Leakage Condition:	2min/20c
Dissipation Factor:	16%
Impedance Ratio -25C:	2.0
Impedance Ratio -40C:	4.0
Ripple 120Hz @ rated temp:	0.07 A
Ripple 120Hz @ alt temp:	0.0952 A
Ripple 120Hz alt temp:	50C