



4 Type

- H Vertical slots
- B Horizontal slots
- HB Horizontal and vertical slots

Metric table

Dimensions in: millimeters - inches											
l ₁	l ₂	d ₁	d ₂	h ₁	h ₂	h ₃	l ₃	m ₁	m ₂	w	
52 2.05	40 1.57	4.5 0.18	4 0.16	9.5 0.37	6 0.24	5.5 0.22	22 0.87	30 1.18	22 0.87	2 0.08	
64 2.52	50 1.97	5.5 0.22	6 0.24	11.5 0.45	7 0.28	6.5 0.26	28 1.10	37 1.46	27 1.06	3 0.12	
76 2.99	60 2.36	6.5 0.26	8 0.31	15 0.59	9 0.35	8.5 0.33	33.5 1.32	42 1.65	34 1.34	4 0.16	

Specification

- Body
Zinc die-cast **ZD**
- Powder coated
Black, RAL 9005, textured finish **● SW**
Silver, RAL 9006, textured finish **● SR**
- Pin
Stainless steel
European Standard No. 1.4305 (AISI 303)
- Adjustment bushings
Zinc die-cast, black powder coated
- RoHS compliant

Information

With GN 127 adjustable alignment hinges, doors and covers can be positioned snugly and in a finely adjusted manner by moving the adjusting bushings. In this way, door gaps can be readjusted and manufacturing tolerances can be compensated. The arrowheads mark the middle of the adjustable range w.

see also...

- List of Hinge Types
- T-Nut Assemblies GN 965 / GN 968
- Adjustable Alignment Hinges GN 238 (Zinc Die-Cast, Adjustable)

How to order

1 2 3 4 5
GN 127-ZD-64-50-HB-SR

- 1 Material
- 2 Width l₁
- 3 Length l₂
- 4 Type
- 5 Finish

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10