т Q Т	m		0		A		
A Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z						4	
						3	
			LAYOUT SHOWN AS EX	(AMPLE			
Keying Shown	as example						
CHARACTERISTICS	Connector dimension						
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 29.4 Max	[					
-Shell Material : Aluminium	Z 31 Max		SOURIAU shall not be liable for any				
-Shell Plating : Nickel -Insulator : Thermoplastic	the Creative time is a state of the Derties on hus third party.						
-Contacts : Copper Alloy			(professional recommendat				
-Seals & Grommet : Silicon Elastomer							
<ul> <li>Contact Plating : Gold over copper Alloy 0.8µm minimum</li> </ul>		CountryJurisdiction & Control ListFRNot Listed2					
-Durability : 500 Mating cycles							
-Delivered with Souriau contacts and Accessories		PN: 8D513F08BB					
-Temperature Range65°C to +200°C						_	
-Salt Spray : 48 hours		A 17-10-2016	First Release				
		ISS DATE	Latest modification - by		MOD N°	,	
		Designed By:	Date:	CUSTOMER DRAW	ING	_	
				TITLEAluminium Plug 8D series			
→ BASIC SERIES: 8D 5 - 13 F 08 B B SHELL TYPE : Plug with RFI Shielding		SCALE -{	General linear Tolerances:	NPRDS / PROJEC	Г	_	
				This document is t		-  '	
CONTACT TYPE       : Standard Crimp Contact       ORIENTATION : B         SHELL SIZE : 13       CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM it must not be reproduce communicated without per				
		FORMAT					
PLATING : F = Nickel	CONTACT LAYOUT : 13-08	A3	SOURIAU		SHEET		
			8D513F0		1/2		
H I G I F	E E	D	C	B	А		

r	Ŧ	۵	г	m		0	
		Contact Layout					
4		$x \left( \begin{array}{c} \bullet & \bullet^{A} \\ \bullet & \bullet^{A} \\ \bullet & \bullet^{H} \\ \bullet & \bullet^{H} \\ \bullet & \bullet^{C} \\ \bullet & \bullet^$					
		Contacts           Contact location           X-axis         Y-axis           D         X-axis         Y-axis         (mm)           A         +.065 (1.65)         +.157 (3.99)         B         +.170 (4.32)         +.000 (0.00)           C         +.120 (3.05)        120 (3.05)        120 (3.05)        120 (3.05)           D        000 (0.00)        170 (4.32)         +.000 (0.00)        170 (4.32)           F        170 (4.32)         +.000 (0.00)        065 (1.65)         +.157 (3.99)           H         +.000 (0.00)         +.044 (1.12)        0044 (1.12)					
ω	Shell Arrangement Nu size no. c 13 -8	imber of Size Service Contact Supersede ontacts contacts rating location 8 20 I All MS20051-					
	-					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda	
N						Count FR PN: 8D513	
					A 17-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
					SCALE	Alumir	
<u> </u>					NA	General linear Tolerances: ±	
					SOURIA		
					FORMAT A3	SOURIAU 8D513F	
	Н	G	F	E \	D	C	

