



3 Type

- A Blank type
- C With plain blind bore, tol. H7
- D With tapped through bore
- E With tapped blind bore

Inch table

1 d ₁	2 d ₂ Thread Type E	d ₄ -0.02	h ₁ -1	h ₂ ≈	t ₁ min.	t ₂
1.57 40	1/4 x 20	5/16 x 18	0.59 15	0.98 25	0.49 12.5	0.59 15
1.97 50	5/16 x 18	3/8 x 16	0.75 19	1.26 32	0.63 16	0.79 20
2.36 60	3/8 x 16	1/2 x 13	0.83 21	1.57 40	0.79 20	1.02 26
2.76 70	1/2 x 13	5/8 x 11	1.02 26	1.81 46	0.91 23	1.26 32

Dimensions in: inches - millimeters

Metric table

1 d ₁	2 d ₂ Thread Type E	Type D / Type E	2 d ₃ H7 Bore Type C	d ₄ -0.5	h ₁ -1	h ₂ ≈	t ₁ min.	t ₂
					Type A	Type C / Type D / Type E		
40 1.57	M 6	M 8	B 8	15 0.59	26 1.02	25 0.98	12.5 0.49	15 0.59
50 1.97	M 8	M 10	B 10	19 0.75	33 1.30	32 1.26	16 0.63	18 0.71
60 2.36	M 10	M 12	B 12	21 0.83	41 1.61	40 1.57	20 0.79	22 0.87
70 2.76	M 12	M 16	B 16	26 1.02	47 1.85	46 1.81	23 0.91	28 1.10

Dimensions in: millimeters - inches

Specification

- Aluminum
 - Matte, tumbled finish **MT**
 - Flash mark not visible
 - Polished finish **PL**
(only available in Type C, D, E in metric sizes)
- RoHS compliant

On request

- Special threads, bores, or threaded studs in matte finish only
- Other modifications such as cross holes and set screw holes

Information

GN 5336 star knobs are forged; therefore, a close grain structure is maintained providing a high tensile strength and a smooth surface. Casting flash is eliminated through high quality production techniques. Original ELESA design, now produced in metal in agreement with ELESA S.p.A.

How to order (Blank type)	1 Handle diameter d ₁
GN 5336-50-A-MT	3 Type
	4 Finish

How to order (Inch)	1 Handle diameter d ₁
GN 5336-40-1/4X20-E-MT	2 Thread d ₂
	3 Type
	4 Finish

How to order (Metric)	1 Handle diameter d ₁
GN 5336-60-B12-C-PL	2 Bore d ₃ (Thread d ₂)
	3 Type
	4 Finish