

Number of contacts

4+

230/400 V  
10 A

Han A

| Identification   | Wire cross section (mm <sup>2</sup> ) | Part number    |                | Drawing<br>Dimensions in mm   |
|--|---------------------------------------|----------------|----------------|---|
|  |                                       | male           | female         |   |
| <p> Han-Quick Lock®<br/>Han A®,<br/>Han-Quick Lock® termination</p> <p>Blue slide</p>  | 0.5–2.5                               | 09 20 004 2633 | 09 20 004 2733 | <p>Dimensions: 37,5, 32, 23,7, 23,7, 21, 21, 36,7, 31,2</p> <p>Contact arrangement (view from termination side)</p> |
| <p> Han-Quick Lock®<br/>Han A®,<br/>Han-Quick Lock® termination</p> <p>Black slide</p> | 0.25–1.5                              | 09 20 004 2634 | 09 20 004 2734 | <p>Dimensions: 21, 21, 36,7, 31,2</p> <p>Contact arrangement (view from termination side)</p>                       |
| <p>Han A®,<br/>Screw terminal</p>  | 0.75–1.5                              | 09 20 004 2611 | 09 20 004 2711 | <p>Dimensions: 21, 27,7, 27, 21</p> <p>Contact arrangement (view from termination side)</p>                         |