

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

M

M

L

L

K

K

J

J

I

I

H

H

G

G

F

F

E

E

D

D

C

C


B

B

A

A

VIEW ON MATING SIDE



A = 32 STANDARD CONTACTS L = 3
 C = 32 STANDARD CONTACTS L = 3
 S = 64 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G1/O = CONTACT AREA LEVEL 1 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 2

C	G1/O	c1-32
A	G1/O	a1-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

24-border.DGN REV A
 96/06/12 LEVEL 6

19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1

EC NO. J 2004-XXXX DRAWN BY: 09/09/03 CHECKED BY: 09/09/03 APPROVED BY: 09/09/03	QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	DIMENSIONS:	SHT REV
		<input type="checkbox"/> mm <input type="checkbox"/> INCH	<input type="checkbox"/> mm <input type="checkbox"/> INCH	<input checked="checked" type="checkbox"/> mm <input type="checkbox"/> INCH	<input type="checkbox"/> mm <input type="checkbox"/> INCH		
	MAJOR	\pm	\pm	N.S.	09/09/03	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT	REVISE ON CAD ONLY
	CRITICAL	\pm	\pm	G.L.	09/09/03		
		\pm	\pm	G.L.	09/09/03		
REV	DESCRIPTION	ANGULAR: \pm	CAD FILENAME	MATERIAL NO.	DRAWING NO.	SHEET NO.	
C			SD-85003-0282.S0	85003-0282	SD-85003-0282	1 OF 1	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.					