VIEW ON MATING SIDE

| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31 | 32 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| c | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A |
| b | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A |
| a | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A | A |

A = 96 STANDARD CONTACTS L = 2

| | |
|---|---|
| MARKING | STANDARD |
| PERFORMANCE LEVEL | G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN |
| FLUX PROOF | NO |
| FIXING CLIP | NO |
| DIMENSIONS | 610-6043-201 SHT 1 |

| | | |
|---|---|---|
| A | G2/0 | a1-32 b1-32 c1-32 |
| CONTACT SYMBOL | PERFORMANCE LEVEL | CONTACT POSITION NUMBER |

ENTER DESCRIPTION
EC NO: I2009-0099
DRWN:SJ 2008/09/16
CH'KD:KPRASAD 2008/09/16
APPR:KPRASAD 2008/09/16
DESCRIPTION
A
REV

QUALITY SYMBOLS
▼=0
(C)=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

| | mm | INCH |
|---|---|---|
| 4 PLACES | ± --- | ± --- |
| 3 PLACES | ± --- | ± --- |
| 2 PLACES | ± --- | ± --- |
| 1 PLACE | ± --- | ± --- |
| ANGULAR ±---° | | |

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: SUMESH DATE: 2008/09/02
CHECKED BY: KPRASAD DATE: 2008/09/02
APPROVED BY: KPRASAD DATE: 2008/09/02

TITLE: 96 POS. MALE CONNECTOR ACC. DIN 41612 STYLE R CONTACTS

molex MOLEX INCORPORATED

MATERIAL NO.: 850130189
DOCUMENT NO.: SD-85013-0189
SHEET NO.: 1 OF 1
SIZE: A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION