Г	I G I	т		0	Ξ	A	
4	Z T T T T T T T T T T T T T						4
ယ				LAYOUT SHOWN AS E	XAMPLE		3
	Keying Sho	own as example					
	CHARACTERISTICS	Connector dimension					
	Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
2	Material Aluminium ØS 29.4 Max SOURIAU shall not be liable for any non-conformity or damage Bell Plating : Olive drab Cadmium VV THREAD M18x1-6g UV THREAD M18x1-6g ulator : Thermoplastic : Copper Alloy : Copper Alloy 0.8 µm minimum VV THREAD M18x1-6g als & Grommet : Silicon Elastomer : Gold over copper Alloy 0.8 µm minimum Image: Country Super Alloy 0.8 µm minimum Jurisdiction & Control List						2
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D513W26BN			
	-Temperature Range -65°C to +175°C		A 19-10-2016	First Release			
	-Salt Spray : 500 hours -Mass : 27.44 g ± 10%		ISS DATE	Latest modification - by		MOD N°	<u> </u>
	11035 . 27.44 5 ± 10/0		Designed By:	Date:	CUST	OMER DRAWING	
			TITLE	TITLE Aluminium Plug 8D series			
	BASIC SERIES: 8D 5 - 13 W 26 B N SHELL TYPE : Plug with RFI Shielding - 13 W 26 B N		SCALE	General linear Tolerances: ±	NP	RDS / PROJECT 859	1
	CONTACT TYPE : Standard Crimp Contact		SOURIAU This document is the property of SOURIAU it must not be reproduced or				
	SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings)			COLUDIALLODO NIS			
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT	-: 13-26 FORMAT A3	SOURIAU		SHEET	
		E	D A3	8D513W	20BIN-C	1/2	

ŗ		G	г П	m	D	0
4		Contact Layout 26				
_		2#12 6#22D				
ω	Ctc A B C D E F 1 2	13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 -4.34 3.25 0 -3.25 0				
	F				[
2						SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat Countr FR
					A 19-10-20	PN: 8D513V
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumin General linear
_					NA	Tolerances:
					SOURIA	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D513W
l	Н	G	F	E	D	C
					W	

