

Specification Sheet

Part Number: TSRP2I-6A



One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Ivory, 120ft/Carton

Article Number	250-62601
Type	TSRP2-6A
Color	Ivory (IV)
Features & Benefits	<ul style="list-style-type: none">•Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick re-entry as well as providing a secure installation of power cables.•U.L. Listed for power up to 600 Volts, meeting UL5A and CSA 22.2 Number 62-93 Standards.•Manufactured from UL 94V-0 rated PVC material.•Fittings incorporate a minimum 1" bend radius per TIA/EIA 568-B and 569-A standards.•Large base for greater adhesive surface.•Rubber-based foam tape adhesive with high ultimate bond strength, which conforms to any surface.•Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking.•Junction boxes can be used for electrical or data outlets.•Designed to complement HellermannTyton's industry standard TSR low voltage raceway system.
Quantity Per	carton

Product Description

HellermannTyton's TSRP power surface raceway is a one piece, non-metallic, adhesive backed latching raceway designed to aesthetically organize and route either power or communications cables. Completely tamper resistant, the cover's self-locking, hidden positive latch permits quick reentry as well as providing a secure installation of power cables.

Short Description

One Piece Power Rated Raceway, 1-1/4", 6.0 ft Long, PVC, Ivory, 120ft/Carton

Global Part Name

TSRP2-6A-PVC-BGE

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

1.25

Width W (Metric)

31.75

Height H (Imperial)

.75

Height H (Metric)

19.05

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Halogen free

No

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Package Quantity(Imperial)

120

Package Quantity (Metric)

36.58

Customs Number

3925900000