Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

$$\label{eq:max-ey} \begin{split} \text{Max-Eyth-Straße 1} & \cdot \text{74638 Waldenburg} \cdot \text{Germany} \\ \text{Tel.} & +49 (0) \, 79 \, 42 \, 945 - 0 \cdot \text{Fax} \\ & +49 (0) \, 79 \, 42 \, 945 - 400 \\ \text{eiSos@we-online.de} \cdot \text{www.we-online.de} \end{split}$$



Product / Process Change Notification (PCN)						
☐ Major change☑ Minor change						
PCN #:	PCN_ConBHD_20210813	Change Category:				
Affected Series:	WE-ConBHD; 6120xx22921_6120xx22121	□ Equipment / Location□ General Data□ Material				
PCN Date:	May 12, 2021	☐ Process				
Effective Date:	August 13, 2021	□ Product Design☑ Shipping / Packaging□ Supplier□ Software				
Contact:	Product Management	Data Sheet Change:				
Phone:	+49 (0) 7942 - 945 5001	⊠ Yes □ No				
Fax:	+49 (0) 7942 - 945 5179	Attachment:				
E-Mail:	pcn.eican@we-online.com	□ Yes ⊠ No				
DESCRIPTION AND	D PURPOSE OF CHANGE:					
Due to packaging or	otimizations, Würth Elektronik will change the pac	kaging quantities				
All products with dat	te code 2021-05-01 or later, will be affected by thi	s change.				
There will be no cha	inge in form, fit, function, quality or reliability of the	e product.				

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions

$$\label{eq:max-ey} \begin{split} \text{Max-Eyth-Straße 1} & \cdot \text{74638 Waldenburg} \cdot \text{Germany} \\ \text{Tel.} & +49 \text{ (0)} \text{ 79} \text{ 42} \text{ 945-0} \cdot \text{Fax} \text{ +49 (0)} \text{ 79} \text{ 42} \text{ 945-400} \\ \text{eiSos@we-online.de} & \cdot \text{www.we-online.de} \end{split}$$



DETAIL OF CHANGE:

Number of tray per carton will pass from 11 to 10.

BEFORE AFTER

POLARITY	PCS/TRAY	Г	TRAY/CARTON	PCS/CARTON
10	182	Γ	11	2002
14	154	L	11	1694
16	140	Г	11	1540
20	126		11	1386
24	112	L	11	1232
26	112	L	11	1232
30	98	L	11	1078
34	84		11	924
40	84		11	924
50	70	L	11	770
60	56		11	616
64	56	L	11	616
			•	·

POLARITY	PCS/TRAY		TRAY/CARTON	PCS/CARTON
10	182	Г	10	1820
14	154	Г	10	1540
16	140	Г	10	1400
20	126	Г	10	1260
24	112	Г	10	1120
26	112	Г	10	1120
30	98	Г	10	980
34	84	Г	10	840
40	84	Г	10	840
50	70	Γ	10	700
60	56	Г	10	560
64	56	Г	10	560

RELIABILITY / QUALIFICATION SUMMARY:

There will be no change of the product, therefore no additional reliability or qualification testing will be performed.