

Specification Sheet

Part Number: 181-00582



Slotted Wall Wiring Duct, 2" X 3", Adhesive, PVC, Gray, 120ft/Carton

Article Number

181-00582

Type

SLA2X3

Color

Gray (GY)

Features & Benefits

- Strong fingers prevent unwanted breaking.
- Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct.
- Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.

Quantity Per

carton

Product Description

Pro-Duct slotted wall wiring duct features break-away fingers which provide additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a wider opening is required. The lower score line allows the sidewall to be smoothly cut for joints and "T's".

Short Description

Slotted Wall Wiring Duct, 2" X 3", Adhesive, PVC, Gray, 120ft/Carton

Global Part Name

SLA2X3-PVC-GY

Technical Description

Adhesive

Length L (Imperial)

6.0

Length L (Metric)

1.83

Width W (Imperial)

2.0

Width W (Metric)

50.8

Height H (Imperial)

3.07

Height H (Metric)

77.90

Mounting Hole Centers (Imperial)

4.0

Material

Polyvinylchloride (PVC)

Material Shortcut

PVC

Flammability

Self-Extinguishing

Halogen free

No

Operating Temperature (Metric)

+122°F (+50°C)

Reach Complaint(Article 33)

No

| | |
|--|--|
| ROHS Complaint | Yes |
| Certification/Specification WEB | EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A CSA |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 120 |
| Package Quantity (Metric) | 36.58 |
| Customs Number | 3925900000 |