

## Housing - HC-EVO-B10-HLFD-EL-AL - 1411455

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B10, for double locking latch, height: 64 mm, without EVO screw connection.

### Product Features

- Flexible cable outlet direction, lateral or straight



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 140.0 g  |
| Custom tariff number                 | 85389099 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|        |       |
|--------|-------|
| Height | 64 mm |
| Width  | 44 mm |
| Length | 73 mm |

#### Ambient conditions

|  |                           |
|--|---------------------------|
| Degree of protection of housing (IP)   | IP66                      |
|  | IP69K (ISO 20653:2013-02) |
| Degree of protection of housing (NEMA) | 4                         |
|  | 4X                        |
|  | 12                        |
| Ambient temperature (operation)        | -40 °C ... 125 °C         |

# Housing - HC-EVO-B10-HLFD-EL-AL - 1411455

## Technical data

### General

|                          |  |
|--------------------------|--|
| Note                     | For contact inserts HC-B10, BB18, DD42, M, K8/24   |
| Size                     | B10  |
| Housing type             | Sleeve housing   |
| Locking type             | For double locking latch   |
| No. of cable outlets     | 1  |
| Cable exit               | straight   |
|                          | Lateral  |
| Screw connection         | none   |
| Housing material         | Die-cast aluminum, salt water resistant  |
| Housing surface material | Uncoated   |
| Connection               | The sleeve base housing must be supplemented with the EVO screw connection. The EVO screw connection is available in 4 sizes. It enables the creation of a straight or a lateral cable outlet. The EVO screw connection is assembled by hand or using a pipe wrench. |

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143424 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

## Approvals

### Approvals

---

Approvals

GL / EAC

---

Ex Approvals

---

Approvals submitted

## Housing - HC-EVO-B10-HLFD-EL-AL - 1411455

### Approvals

---


#### Approval details

GL

EAC

### Drawings

Dimensional drawing



#### Dimensional drawing

---