



- NOTES:
1. KNOB AND HARDWARE SHIPPED UNASSEMBLED.
  2. MAX PANEL THICKNESS: 0.25 [6.4]
  3. MATERIALS:  
 FRAME - CRS, ZINC PLATED  
 BUSHING & ACTUATOR - COPPER ALLOY, NICKEL PLATED  
 SPRINGS - SPECIAL COPPER ALLOY  
 TERMINALS - TINNED DIPPED SOLDER LUGS  
 INSULATORS - PHENOLIC  
 LIFTERS & ROLLERS - THERMOPLASTIC  
 SCREWS - CRS, NICKEL PLATED  
 HEX NUT - COPPER ALLOY, NICKEL PLATED  
 WASHER - CRS, NICKEL PLATED  
 KNOB - THERMOPLASTIC, BLACK
  4. THIS PRODUCT IS RoHS COMPLIANT

CUSTOMER DRAWING

REV	ECO NUMBER	DATE	BY	APVD
A	27887	05-12-17	PC	TJK
REVISIONS				

★ STAR SYMBOL DENOTES CRITICAL DIMENSION

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES  
 -TWO PLACE DECIMALS ±0.01  
 -THREE PLACE DECIMALS ±0.005  
 -ANGLES ±1°  
 -ALL DIA. CONCENTRIC WITHIN 0.005 T.I.R.
2. FEATURES ON THE SAME CENTERLINE MUST BE ALIGNED WITHIN ±0.002
3. REMOVE ALL BURRS

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
SIZE	WIDTH	MULT	LBS/M	TEMPER
FINISH		MATERIAL		
SPEC No.		SPEC No.		
FIRST USED ON		SCALE		
		2:1		
DATE DRAWN	BY	CHKD	APVD	
May-14-19	PC	PC	TJK	
		05-14-19	05-14-19	
NAME				PART No.
LT SERIES LEVER SWITCH				41212LX
2 POSITION LOCKING, RoHS				REV
				A