

# SERVO MOTOR CABLES



## SL 841 C TPE motor connection cable with 1 or 2 pairs and overall tinned copper screen 0.6/1 kV

AWM Style 20235 80°C CSA AWM I/II A/B 80°C 300V FT1 FT2 CE



Marking for SL 841 C 08410407: SAB BRÖCKSKES · D-VIERSEN ·

08410407 SL 841 C 4 x 0.75 mm<sup>2</sup> (1000V) + 2 x (2 x 0.34 mm<sup>2</sup>) (300V) **DESINA** AWM Style 20235 80°C CSA AWM I/II A/B 80°C 300V FT1 FT2 CE

The SL 841 C is a halogen-free UL recognized and CSA approved, overall shielded continuous flex power supply and feedback cable which has been designed for automated servo systems. This composite cable offers a unique combination of signal and power conductors, under one jacket, while reducing weight and saving space. The special design makes SL 841 C ideally suited for automated applications, such as cable track, automated handling equipment, pick-and-place units, gantry robots, machine tools and other continuous movement applications. An overall tinned copper braid is recommended whenever electrical interference distorts signal transmission, or when EMI emission needs to be suppressed.

### Construction:

<b>Conductor:</b>	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6 < 20 AWG with reference to DIN VDE 0812
<b>Insulation:</b>	TPE
<b>Color code:</b>	black conductors with consecutive numbers acc. to EN 50334 and a green-yellow earth wire.
<b>from item no. 08411415:</b>	supply conductors: * U1, V2, W3 and a green-yellow earth wire control conductors: ** BR1 and BR2
<b>Stranding:</b>	control conductors 22 - 14 AWG twisted to pairs
<b>Screen:</b>	pairs wrapped with Alu-foil, tinned copper braid
<b>Wrapping:</b>	pairs with PETP foil
<b>Stranding:</b>	screened control pairs and supply conductors twisted together in layers
<b>Wrapping:</b>	two layers non-woven tape
<b>Screen:</b>	tinned copper braiding
<b>Wrapping:</b>	non-woven tape
<b>Jacket material:</b>	TPMU acc. to DIN EN 50363-10-2 with mat surface
<b>Jacket color:</b>	orange

### Technical data:

<b>Nominal voltage:</b>	supply conductors U <sub>0</sub> /U 0.6/1 kV	
<b>Voltage UL/CSA:</b>	supply conductors 1000V	
<b>Peak operating voltage:</b>	control conductors max. 350 V	
<b>Voltage UL/CSA:</b>	control conductors 300 V	
<b>Testing voltage:</b>	supply conductors 4000 V	control conductors 1500 V
<b>Min. bending radius</b>		
<i>fixed installation:</i>	5 x O.D.	
<i>free movement:</i>	10 x O.D.	
<i>for continuous flexing:</i>	12 x O.D.	
<b>Radiation resistance:</b>	5 x 10 <sup>7</sup> cJ/kg	
<b>Temperature range</b>	<b>DIN VDE</b>	<b>UL/CSA:</b> up to +80°C
<i>static:</i>	-50/+90°C	
<i>flexing:</i>	-40/+90°C	
<b>Burning characteristics:</b>	flame retardant and self-extinguishing acc. to IEC 60332-1-2, EN 60332-1-2, UL FT1 and CSA FT1 FT2	
<b>Oil resistance:</b>	very good acc. to DIN VDE 0282 part 10 + HD 22.10	
<b>Chemical resistance:</b>	good against acids, alkalines, solvents, hydraulic liquids etc.	
<b>Weather resistance:</b>	very good	
<b>Absence of harmful substances:</b>	acc. to RoHS directive of the European Union see page O/30	

### Outstanding features:

- UL recognition, CSA approval
- very good EMC characteristics
- long service life
- adhesion-free installation
- suitable for cable tracks
- halogen-free
- free from paint wetting disruptive substances (LABS - free)
- flexible at low temperatures
- in accordance with Indramat INK and Siemens 6FX8008



**Cable harnessing possible on request.**

item no.	power conductors	single pairs, individually shielded	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ 08410407	19 AWG / 4c	22 AWG / 2pr	0.457 ± 0.020	11.6 ± 0.5	113
▶ 08410410	18 AWG / 4c	19 AWG / 2pr	0.465 ± 0.020	11.8 ± 0.5	135
▶ 08410415	16 AWG / 4c	19 AWG / 2pr	0.484 ± 0.020	12.3 ± 0.5	153
▶ 08410425	14 AWG / 4c	18 AWG / 2pr	0.571 ± 0.031	14.5 ± 0.8	215
▶ 08410441	12 AWG / 4c	18 AWG / 1pr			
		+ 16 AWG / 1pr	0.685 ± 0.024	17.4 ± 0.6	308
▶ 08410461	10 AWG / 4c	18 AWG / 1pr			
		+ 16 AWG / 1pr	0.744 ± 0.031	18.9 ± 0.8	374
▶ 08410471	8 AWG / 4c	18 AWG / 1pr			
		+ 16 AWG / 1pr	0.803 ± 0.039	20.4 ± 1.0	495
▶ 08410485	6 AWG / 4c	16 AWG / 2pr	1.024 ± 0.031	26.0 ± 0.8	747
▶ 08410490	4 AWG / 4c	16 AWG / 2pr	1.157 ± 0.031	29.4 ± 0.8	1019
▶ 08410495	2 AWG / 4c	16 AWG / 2pr	1.232 ± 0.031	31.3 ± 0.8	1265
▶ 08410496	1 AWG / 4c	14 AWG / 2pr	1.504 ± 0.031	38.2 ± 0.8	1787

item no.	power conductors	single pairs, individually shielded	nominal outer-ø inch	mm	cable weight ≈ lbs/mft
▶ 08411415	16 AWG / 4c	16 AWG / 1pr	0.492 ± 0.012	12.5 ± 0.3	149
▶ 08411425	14 AWG / 4c	16 AWG / 1pr	0.524 ± 0.016	13.3 ± 0.4	192
▶ 08411440	12 AWG / 4c	16 AWG / 1pr	0.598 ± 0.016	15.2 ± 0.4	248
▶ 08411460	10 AWG / 4c	16 AWG / 1pr	0.654 ± 0.043	16.6 ± 1.1	326
▶ 08411470	8 AWG / 4c	16 AWG / 1pr	0.768 ± 0.063	19.5 ± 1.6	455
▶ 08411480	6 AWG / 4c	16 AWG / 1pr	0.933 ± 0.039	23.7 ± 1.0	685
▶ 08411490	4 AWG / 4c	16 AWG / 1pr	1.071 ± 0.028	27.2 ± 0.7	953
▶ 08411495	2 AWG / 4c	16 AWG / 1pr	1.185 ± 0.039	30.1 ± 1.0	1216
▶ 08411496	1 AWG / 4c	16 AWG / 1pr	1.354 ± 0.039	34.4 ± 1.0	1655

Other dimensions and colors are possible on request.

BOSCH REXROTH / INDRAMAT is a registered trademark, which is used for comparative purposes only  
SIEMENS is a registered trademark, which is used for comparative purposes only

**E-mail: info@sabcable.com**



**Web site: www.sabcable.com**