| ت س | т (П | | 0 | Φ | A | |
|--|---|----------------------------|---|--|-----------------|--|
| Image: state | ØS- | | | | | |
| ω | | | LAYOUT SHOWN AS EX/ | AMPLE | | |
| CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III | Keying Shown as example Connector dimension Dim Nominal |] | | | | |
| -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minim | ØS 35.7 Max Z 31 Max VV THREAD M25x1-6g | | SOURIAU shall not be liable for any due to a use of the Products whic the Specifications issued by either of t (professional recommendation Country FR | ch does not comply with the Parties or by a third party on, technical notice.) | | |
| -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C | | A 14-10-2016 | PN: 8D517F | 06AD | | |
| -Salt Spray : 48 hours | | ISS DATE Designed By: | Latest modification - by Date: | CUSTOMER DRAWIN | MOD N° | |
| | TITLE Aluminium Plug 8D series | | | | | |
| BASIC SERIES: 8D 5 - 17 → SHELL TYPE : Plug with RFI Shielding | F 06 A D | SCALE - | General linear Tolerances: ± | NPRDS / PROJECT 859 | | |
| CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17 | ORIEN CONTACT TYPE : PIN(50 | ITATION : D O0 Matings) | WWW.SOURIAU.CO | This document is the SOURIAL it must not be rep communicated witho | J roduced or | |
| PLATING : F = Nickel | CONTACT LAY | DUT : 17-06 | SOURIAU 8D517F0 | DRG N° | SHEET 1/2 | |
| H G | F E | D | C | | A | |

| | | | G | г | т | | | 0 | |
|---|------------------------|--|--|------------------|------|-------------------|-------|---|---|
| | | Contac | ct Layout | | | | | | |
| 4 | | -x (D + F | $ \begin{array}{c} \bullet \\ A \\ \oplus \\ \oplus \\ \end{array} \\ \end{array} \\ \begin{array}{c} \bullet \\ \bullet $ | | | | | | |
| | | Contact Contact | €Y ntacts ngement 17-6) Location | | | | | | |
| ယ | Shell An Size 17 | A +.121 B +.241 C +.000 D241 E121 F +.000 angement Number of contacts co | m) (mm) (3.07) + 209 (5.31) (6.12) + .000 (0.00) (0.00)241 (6.12) (6.12) + .000 (0.00) (3.07) + .209 (5.31) (0.00) + .000 (0.00) Size Service Contact Superint ntacts rating location | rsedes 0053-6 | | | | | |
| | | | | | | | | SOURIAU shall not b due to a use of th the Specifications issue | e Products w ed by either c |
| 2 | | | | | | | | (professional | recommenda Count FR |
| | | | | | | A ISS Desig | | First Release Latest modification - b Date: | 8D517 |
| | | | | | | SC | TITLE | | Alumir General linear Tolerances: |
| 1 | | | | | | | URIAU | WWW.SO | URIAU.(|
| | | 1 | | | | A | | 3 | OURIAU 3D517F |
| | Н | | G | F | E | D | | С | |

