

## Specification Sheet

Part Number: 170-20400



Helagaine Braided Sleeving, 4 mm Dia, PA66, GY, 656ft/Reel

**Article Number**

170-20400

**Type**

HEGPA6604

**Color**

Gray (GY)

**Features & Benefits**

- Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture.
- Material performs well in wet applications and where abiding substrate has a smooth surface.

**Quantity Per**

metre

**Product Description**

Helagaine Nylon Polyamide Expandable Braided Sleeving is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.

**Short Description**

Helagaine Braided Sleeving, 4 mm Dia, PA66, GY, 656ft/Reel

**Global Part Name**

HEGPA6604-PA66-GY

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Length L (Imperial)</b>            | 656.0                             |
| <b>Length L (Metric)</b>              | 200.0                             |
| <b>Bundle Diameter Min (Imperial)</b> | 0.12                              |
| <b>Bundle Diameter Min (Metric)</b>   | 3                                 |
| <b>Bundle Diameter Max (Imperial)</b> | 0.24                              |
| <b>Bundle Diameter Max (Metric)</b>   | 6                                 |
| <b>Diameter D (imperial)</b>          | 0.16                              |
| <b>Diameter D (metric)</b>            | 4.1                               |
| <b>Nominal Diameter (Imperial)</b>    | 5/32                              |
| <b>Nominal Diameter (Metric)</b>      | 4                                 |
| <b>Material</b>                       | Polyamide 6.6 (PA66)              |
| <b>Material Shortcut</b>              | PA66                              |
| <b>Flammability</b>                   | UL 94 V2 FMVSS 302                |
| <b>Halogen free</b>                   | Yes                               |
| <b>Operating Temperature (Metric)</b> | -76°F to +302°F (-60°C to +150°C) |

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** EN [45545-2]:2013

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 656

**Package Quantity (Metric)** 200

**Customs Number** 3926909987

**Content Unit(BMEcat)** metre

**Weight (Metric)** 0.5

**Weight (Imperial)** 1.1