

Datasheet for part number CA3100E24-20SB0514

Our Catalog Part Number: CA3100E24-20S-B-05-14

Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA BAYONET

Connector with bayonet coupling
Box mounting receptacle (rear mount, through holes in flange)
Shielded connector with endbell for shielded braids and heat shrinkable boots
Socket
24
24-20
2 contacts size 25, 9 contacts size 15
Metric Crimp
Hard silver
yes
22 A
41 A
6 mΩ
3 mΩ
2,0-3,0 mm² (Size 25), 0,75-0,5 mm² (Size 15)
In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41.
Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ
2500 Vrms
2,8 mm
Standard insulator material -55°/+125°C (-67/257°F)
IP67 acc. to DIN 40 050 and IP68 (1 bar pressure for 16h)
500 hours salt spray resistant
500 min
1,0 N
1,5 N
For infos on Gauge please see catalog VG95234, part 1
Closing: 14 Nm max / Opening: 0,8 Nm min
35 N
55 N
Aluminium alloy
Olive drab chromate over cadmium plating (conductive)
CR-Elastomere
Copper alloy

Specifications and dimensions subject to change.



Datasheet for part number CA3100E24-20SB0514

Our Catalog Part Number: CA3100E24-20S-B-05-14		
Brand: Cannon Product Category: Circular Product Line: CA Bayonet	Series: CA BAYONET	

Product Datasheet	
Harnessing Info: Insulator Diameter	See assembly instruction
Wire Stripping (Size 15/15S/16/16S)	6,2 mm
Wire Stripping (Size 25/12)	6,2 mm
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210