

855-14204



Article Number: 855-14204

Description: Connector, Fiber Optic ST Singlemode 900µm, 2mm, 3mm Simplex–Epoxy & Polish

Base Data	Local Order Number	FCSTSM
	Type	FCSTSM
	Features and benefits	<ul style="list-style-type: none"> • Use with epoxy or anaerobic adhesives for different applications or user preference. • Pre-radiused zirconia ceramic ferrules provide precision installation. • Meet ANSI/TIA/EIA 568-C standards. • Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.
	Quantity Per	bag
	Product Description	<p>Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation.</p> <p>Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing</p>
	Technical Description	ST Single Mode Fiber Connector
	Short Description	Connector, Fiber Optic ST Singlemode 900µm, 2mm, 3mm Simplex–Epoxy & Polish
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		1
Customs Number(Schedule B)		8536700000

855-14204

HellermannTyton
