

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35°C TO + 85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C
	VOLTAGE	50V AC	APPLICABLE CONNECTOR	DF21-20S-0.6V(05)
	CURRENT	AWG40 : 0.3A AWG36 : 0.5A	APPLICABLE CONTACT	THIN COAXIAL RIBBON CABLE

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

--	--	--	--	--

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
-------	--------------------------	----------	---------	------

REMARKS NOTE 1:INCLUDING THE TEMPERATURE RISING BY CURRENT. Unless otherwise specifid , refer to JIS C 5402.	APPROVED	TY. OMA	06. 02. 04
	CHECKED	HK. UMEHARA	06. 02. 04
	DESIGNED	SZ. ONO	06. 02. 03
	DRAWN	SZ. ONO	06. 02. 03

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-163694-01
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DF21-20P-0.6SD-GND(05)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL687-2500-6-05	△ 1/1