



Datasheet for part number CIR06AF-20-29S-F80-T29-V0

|   |
|---|
| Our Catalog Part Number: CIR06AF-20-29S-F80-T29-V0  |
| Our Global Manufacturing Part Number: 000698830   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|   |  |
|---|--|
| Product Datasheet                                     |  |
| SERIES  | Connector with Bayonet Coupling  |
| Shell Style   | Straight Plug Connector  |
| Environmental Class                                   | Backshell with A style clamp and bushing   |
| Shell Size  | 20   |
| Contact Arrangement                                   | 20-29  |
| Total Number of contacts                              | 17 contacts  |
| Number of Contacts Size 16                            | 17 contacts size 16  |
| Gender  | Socket   |
| Contact Type  | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                       | Silver   |
| Shell Material  | Aluminium alloy  |
| Shell Plating   | Electroless Nickel (conductive)  |
| Contacts included                                     | no, delivery without contacts  |
| Shock Resistance                                      | Waterproof to 10 meteres (33 ft)<br>12 h (14.7 PSI)  |
| Coupling  | 2000 couplings minimum   |
| Service Rating Letter                                 | A  |
| Operating Voltage DC                                  | 700 V  |
| Operating Voltage AC                                  | 500 V  |
| Dielectric strength -<br>Minimum Flashover AC RMS     | 2800 V   |
| Dielectric strength -<br>Test Voltage AC RMS (Hi Pot) | 2000 V   |
| Note  | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General   | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |