



PIN ASSIGNMENT

P1		P2
A2	-----	A2
A3	-----	A3
A5	-----	A5
A6	-----	A6
A7	-----	A7
A8	-----	A8
B8	-----	B8
A10	-----	A10
A11	-----	A11
B2	-----	B2
B3	-----	B3
B5	-----	B5
B11	-----	B11
B10	-----	B10
A1+B1+A4+B4	-----	A1+B1+A4+B4
+A9+B9+A12+B12	-----	+A9+B9+A12+B12
SHELL	-----	SHELL

5	NUT BLACK PVC 27P MOLDED.	
4	OVERMOLD BLACK PVC 45P MA-001.	
3	USB3.1 C TYPE FEMALE BLACK INSULATOR SOLDER TYPE.	
2	USB3.1 C TYPE MALE BLACK INSULATOR SOLDER TYPE.	
1	(32AWG*1C+EAM)*4+32AWG*1P+32AWG*4C+2EAB(85%) OD:4.8MM L:300mm BLACK PVC JACKET UL2725.	
NO.	Description	P/N

NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
  - (a). 100% OPEN, SHORT & MISWIRE TEST,
  - (b). INSULATOR RESISTANCE: 10 Mohm MIN.  
DC 300V 0.01sec.
  - (c). CONTACT RESISTANCE: 3ohm MAX.

DWG NO:	PCM-0165	GOODS CODE		Draw	Jason	Date	2019/3/15
ITEM NO.		DRAWING EVIDENCE		Check		Date	
Goods NO.				Approval		Date	
Original NO.		Unit(mm)					

PREMIER CABLE MFG CO LTD

D		
C		
B		
VER.A	REVISE	Date.