


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 46.7              |
| B   | 24.05             |
| C   | 4                 |
| D   | 27                |
| E   | 34.5              |
| F   | 37.8              |
| G   | 12.7              |
| H   | 66                |
| I   | 50.9              |
| K   | 47.6              |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 13  | ENDGEHÄUSE DN / ENDBELL HEATSHRINK  |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification:                                      |
|--|
| Shell Material: Aluminium alloy                              |
| Shell Plating: Olive drab chromate over cadmium (conductive) |
| Insulator Material: CR-Elastomere                            |
| Contact Material: Copper alloy                               |
| Contact Plating: Hard silver                                 |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



Engineered for life  
 ITT CANNON GmbH  
 D - 71384 Weinstadt/Germany

description CA3101E28-11P-B-03  
 Cable connecting plug  
 Endbell for heatshrinkable boots  
 Metric Crimp / Pin / Layout: 28-11

© All rights reserved. Reproduction or issue to third in any form  
 whatever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 2049 10. Mar 21