




DATE	SYM	REVISION RECORD	AUTH	DR.	CK.
7/08/06	A	ADDED "ROHS COMPLIANT" UPDATED MATERIAL NOTE	T.B.	B.S.	
3/24/07	B	DIM. 107.8 WAS 107.9 DIM. 9.5 WAS 8.89 DIM. 50.2 WAS 49.5	T.B.	B.S.	
12/21/12	C	DIM. 16.00 WAS 16.20 DIM. 104.0 WAS 102.0 DIM. 11.20 WAS 11.18	T.B.	B.S.	
2/22/13	D	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	



ORDERING CODE BC12AA


SOLDER LUGS = L
(6") WIRE LEADS = W
9 VOLT TYPE SNAPS = SF
PC PINS = PC



Note: Dimensions in mm. (inches)

SPECIFICATIONS :

Plastic material - polypropylene, PP-1040
 Flammability rating-UL94 HB, UL file no. E216959
 Temperature Range: -10°C to +100°C
 Springs - nickel plated steel spring
 Rivets - Brass, nickel plated
 P.C. Pins - Brass, nickel plated
 Contact resistance: Under 50mΩ for +/- contacts per EIA-540J000
 ROHS 2 COMPLAINT

TOLERANCES (EXCEPT AS NOTED)	 Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735		
DECIMAL + .5 (.020") - .5 (.020")	SCALE NONE	DRAWN BY B.S.	APPROVED BY T.B.
FRACTIONAL + .8 (.030") - .8 (.030")	TITLE TWO "AA" CELL HOLDER		
ANGULAR + 3° - 3°	DATE 2/22/2013	DRAWING NUMBER BC12AAPC	