



Datasheet for part number FRCIR030R16S-8SF80T12

|   |
|---|
| Our Catalog Part Number: FRCIR030R-16S-8S-F80-T12   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|  |  |
|--|--|
| Product Datasheet                                  |  |
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Rear Mount Receptacle - Square flange, with rear thread  |
| Mounting   | Flange with through mounting hole  |
| Environmental Class                                | Backshell includes wire sealing grommet and compression ring   |
| Shell Size   | 16S  |
| Contact Arrangement                                | 16S-8  |
| Total Number of contacts                           | 5 contacts   |
| Number of Contacts Size 16S                        | 5 contacts size 16   |
| Gender   | Socket   |
| Contact Type                                       | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                    | Gold   |
| Shell Material                                     | Aluminium alloy  |
| Shell Plating                                      | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts Size 16S      | 1,0-1,5 mm <sup>2</sup> or AWG 18-16   |
| Contact Rating for Contacts Size 16S               | Maximum Current = 22 A<br>Rated and Test Current = 13 A<br>Potential Drop max. 74 mV   |
| Shock Resistance                                   | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                              | A  |
| Operating Voltage DC                               | 700 V  |
| Operating Voltage AC                               | 500 V  |
| Dielectric strength - Minimum Flashover AC RMS     | 2800 V   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | 2000 V   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |