	ד Q T (100 ב	-	0	₿		
4						4
3			LAYOUT SHOWN AS EXA	MPLE		3
	Keying Shown as example					
	CHARACTERISTICS Connector dimension					
	Dim Nominal ØS 25 Max ØS 25 Max Z 31 Max VV THREAD M15x1-6g SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) s & Grommet Silicon Elastomer					
N	-Contact Plating : Gold over copper Alloy 0.8μm minimum	FR Not Listed			2	
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511W02AD A 17-10-2016 First Release			
l	-Temperature Range65°C to +175°C	Δ 17-10-201				-
	-Salt Spray : 500 hours	ISS DATE	Latest modification - by		MOD N°	
	-Mass : 14.61 g ± 10%	Designed By:	Date:	CUSTOMER DRAWING		
		TITLE Aluminium Plug 8D series				
_	BASIC SERIES: 8D 5 - 11 W 02 A D SHELL TYPE : Plug with RFI Shielding	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		-
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : D	SOURIAL		This document is the pro SOURIAU it must not be reprodu		
	SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)	FORMAT		communicated without p	ermission	
1	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-02	FORMAT	SOURIAU E		SHEET	
		A3	8D511W0	2 M D C	1/2	

r	Ŧ	െ	т	m	D	0
		Contact Layout				
4	.x .0 (2)	95 41mm) (2.41mm)				
	Shell Arrangement no. 11 -2	X-axis Y-axis (mm) (mm) + -0.95 (2.41) 095 (2.41) +.000 (.00)				
cى						
	+					SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						PN: 8D511
					A 17-10-20 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					SCALE	Alumi
_ _					SOURIA	J WWW.SOURIAU.
				-	FORMAT A3	SOURIAU 8D511W
	Н	G	F	E	D	C

