

Specification Sheet

Part Number: 170-03071



Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel

Article Number	170-03071
Type	BSPFR188
Color	Gray (GY)
Features & Benefits	<ul style="list-style-type: none">• Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.• Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
Quantity Per	reel

Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description	Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Gray, 225 ft/reel
Global Part Name	BSPFR188-PET-GY
Length L (Imperial)	225.0
Length L (Metric)	68.6
Bundle Diameter Min (Imperial)	0.094
Bundle Diameter Min (Metric)	2.4
Bundle Diameter Max (Imperial)	0.25
Bundle Diameter Max (Metric)	6.4
Diameter D (imperial)	0.13
Diameter D (metric)	3.2
Nominal Diameter (Imperial)	1/8
Nominal Diameter (Metric)	3.2
Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1 FAR 25 FMVSS 302 Mil-202

Halogen free Yes

Operating Temperature (Metric) -94°F to +257°F (-70°C to +120°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL 94 VW-1

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 225

Package Quantity (Metric) 68.58

Customs Number 3926909987

Weight (Metric) 0.18

Weight (Imperial) 0.4