



OBSOLETE	△ <sub>6</sub>	1,2,39,40	1,2,39,40	101.19 [3.984]	99.06 [3.900]	39	80	9-146311-0
	△ <sub>6</sub>	1,2,38,39	1,2,38,39	98.65 [3.884]	96.52 [3.800]	38	78	8-146311-9
	△ <sub>6</sub>	1,2,37,38	1,2,37,38	96.11 [3.784]	93.98 [3.700]	37	76	8-146311-8
	△ <sub>6</sub>	1,2,36,37	1,2,36,37	93.57 [3.684]	91.44 [3.600]	36	74	8-146311-7
	△ <sub>6</sub>	1,2,35,36	1,2,35,36	91.03 [3.584]	88.90 [3.500]	35	72	8-146311-6
	△ <sub>6</sub>	1,2,34,35	1,2,34,35	88.49 [3.484]	86.36 [3.400]	34	70	8-146311-5
	△ <sub>6</sub>	1,2,33,34	1,2,33,34	85.95 [3.384]	83.82 [3.300]	33	68	8-146311-4
	△ <sub>6</sub>	1,2,32,33	1,2,32,33	83.41 [3.284]	81.28 [3.200]	32	66	8-146311-3
	△ <sub>6</sub>	1,2,31,32	1,2,31,32	80.87 [3.184]	78.74 [3.100]	31	64	8-146311-2
	△ <sub>6</sub>	1,2,30,31	1,2,30,31	78.33 [3.084]	76.20 [3.000]	30	62	8-146311-1
	△ <sub>6</sub>	1,2,29,30	1,2,29,30	75.79 [2.984]	73.66 [2.900]	29	60	8-146311-0
	△ <sub>6</sub>	1,2,28,29	1,2,28,29	73.25 [2.884]	71.12 [2.800]	28	58	7-146311-9
	△ <sub>6</sub>	1,2,27,28	1,2,27,28	70.71 [2.784]	68.58 [2.700]	27	56	7-146311-8
	△ <sub>6</sub>	1,2,26,27	1,2,26,27	68.17 [2.684]	66.04 [2.600]	26	54	7-146311-7
	△ <sub>6</sub>	1,2,25,26	1,2,25,26	65.63 [2.584]	63.5 [2.500]	25	52	7-146311-6
OBSOLETE	△ <sub>6</sub>	1,2,24,25	1,2,24,25	63.09 [2.484]	60.96 [2.400]	24	50	7-146311-5
	△ <sub>6</sub>	1,2,23,24	1,2,23,24	60.55 [2.384]	58.42 [2.300]	23	48	7-146311-4
	△ <sub>6</sub>	1,2,22,23	1,2,22,23	58.01 [2.284]	55.88 [2.200]	22	46	7-146311-3
	△ <sub>6</sub>	1,2,21,22	1,2,21,22	55.47 [2.184]	53.34 [2.100]	21	44	7-146311-2
OBSOLETE	△ <sub>6</sub>	1,2,20,21	1,2,20,21	52.93 [2.084]	50.80 [2.000]	20	42	7-146311-1
	△ <sub>6</sub>	1,2,19,20	1,2,19,20	50.39 [1.984]	48.26 [1.900]	19	40	7-146311-0
	△ <sub>6</sub>	1,2,18,19	1,2,18,19	47.85 [1.884]	45.72 [1.800]	18	38	6-146311-9
	△ <sub>6</sub>	1,2,17,18	1,2,17,18	45.31 [1.784]	43.18 [1.700]	17	36	6-146311-8
	△ <sub>6</sub>	1,2,16,17	1,2,16,17	42.77 [1.684]	40.64 [1.600]	16	34	6-146311-7
	△ <sub>6</sub>	1,2,15,16	1,2,15,16	40.23 [1.584]	38.10 [1.500]	15	32	6-146311-6
	△ <sub>6</sub>	1,2,14,15	1,2,14,15	37.69 [1.484]	35.56 [1.400]	14	30	6-146311-5
	△ <sub>6</sub>	1,2,13,14	1,2,13,14	35.15 [1.384]	33.02 [1.300]	13	28	6-146311-4
	△ <sub>6</sub>	1,2,12,13	1,2,12,13	32.61 [1.284]	30.48 [1.200]	12	26	6-146311-3
	△ <sub>6</sub>	1,2,11,12	1,2,11,12	30.07 [1.184]	27.94 [1.100]	11	24	6-146311-2
	△ <sub>6</sub>	1,2,10,11	1,2,10,11	27.53 [1.084]	25.40 [1.000]	10	22	6-146311-1
	△ <sub>6</sub>	1,2,9,10	1,2,9,10	24.99 [.984]	22.86 [.900]	9	20	6-146311-0
OBSOLETE	△ <sub>6</sub>	1,2,8,9	1,2,8,9	22.45 [.884]	20.32 [.800]	8	18	5-146311-9
	△ <sub>6</sub>	1,2,7,8	1,2,7,8	19.91 [.784]	17.78 [.700]	7	16	5-146311-8
	△ <sub>6</sub>	1,2,6,7	1,2,6,7	17.37 [.684]	15.24 [.600]	6	14	5-146311-7
	△ <sub>6</sub>	1,2,5,6	1,2,5,6	14.83 [.584]	12.70 [.500]	5	12	5-146311-6
	△ <sub>6</sub>	1,2,4,5	1,2,4,5	12.29 [.484]	10.16 [.400]	4	10	5-146311-5
OBSOLETE	△ <sub>6</sub>	1,2,3,4	1,2,3,4	9.75 [.384]	7.62 [.300]	3	8	5-146311-4
	△ <sub>6</sub>	1,2,3	1,2,3	7.21 [.284]	5.08 [.200]	2	6	5-146311-3
	△ <sub>6</sub>	1,2	1,2	4.67 [.184]	2.54 [.100]	1	4	5-146311-2
	△ <sub>6</sub>							

PLATING	ROW M	ROW N	C	B	A	NO. OF POSITIONS	PART NUMBER
	HOLD-DOWN POST CONFIG. LOCATIONS.						

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN T. HOFFMAN 21JUN95	Tyco Electronics Tyco Electronics Corporation Harrisburg, Pa 17105-3608
TOLERANCES UNLESS OTHERWISE SPECIFIED:		020CT95	
DIMENSIONS: mm [INCHES]	0 PLC ± -	1 PLC ± .01	NAME: HEADER ASSEMBLY, MOD II, BREAKAWAY, HIGH TEMP., RIGHT ANGLE, DOUBLE ROW, .100 X.100 CL, W/.025 SQ. POSTS WITH HOLD-DOWN CONFIGURATION.
	2 PLC ± 0.51(.02)	3 PLC ± 0.12(.005)	APPLICATION SPEC W/025 SQ. POSTS WITH HOLD-DOWN CONFIGURATION.
	4 PLC ± 0.012(.0005)	ANGLES ± .005	SIZE: A1
MATERIAL: △ <sub>5</sub>	FINISH: SEE TABLE	WEIGHT: -	CAGE CODE: 00779
			DRAWING NO: 146311
			RESTRICTED TO CUSTOMER DRAWING
			SCALE: 4:1 SHEET 2 OF 2 REV C1