



NOTES: Finish (Plating Thickness in Micro-inches)

1. Brass
2. Thin Gold over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
3. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick
4. Teflon
5. Passivated

No	Description	Material	Finish	Q'ty	Drawing No.	Scale	4/1	Issue	A2	Part No.	Approved	Date	Checked	Date	Drawn	Date	Title
8	Ferrule	Copper	Note 2	1		Dimensions are in Inches				Part No.	Approved	Date	Checked	Date	Drawn	Date	<h1 style="text-align: center;">NTE Electronics</h1> <p style="text-align: center;">SMA Crimp Plug (For RG-58, 58A, 58C, 141, LMR195)</p> <p style="text-align: center;">Drawing No. 06-S003</p> <p style="text-align: center;">File No.</p>
7	Insulator	Note 4	Natural	1	Unless Otherwise Specified				8-30-2013								
6	Contact Pin	Note 1	Note 3	1	Tolerances				8-30-2013								
5	Gasket	Silicone	Red	1	0.5-6 = ±0.2				8-30-2013								
4	Retainer Ring	SUS 304	Note 5	1	6-30 = ±0.4				8-30-2013								
3	Insulator	Note 4	Natural	1	30-120 = ±0.6				8-30-2013								
2	Body	Note 1	Note 2	1	120-315 = ±1				8-30-2013								
1	Shell	Note 1	Note 2	1	315-1000 = ±1.6				8-30-2013								
					1000-2000 = ±2.4												