



**Inch table**

Dimensions in: inches - millimeters

<b>1</b> $d_1$	<b>2</b> $d_2$ Thread	<b>3</b> Length $l$		$d_3$	$h$	$k$
.75 19.1	10 x 24	.50 12.7	1.00 25.4	.50 12.7	.63 16.0	.25 6.4
.75 19.1	1/4 x 20	.75 19.1	1.25 31.8	.50 12.7	.63 16.0	.25 6.4
1.00 25.4	1/4 x 20	1.75 44.5	-	.63 16.0	.75 19.1	.25 6.4
1.00 25.4	5/16 x 18	1.75 44.5	3.00 76.2	.63 16.0	.75 19.1	.25 6.4
1.50 38.1	5/16 x 18	1.75 44.5	3.00 76.2	.75 19.1	1.00 25.4	.31 7.9
1.50 38.1	3/8 x 16	1.75 44.5	3.00 76.2	.75 19.1	1.00 25.4	.31 7.9
2.00 50.8	3/8 x 16	1.75 44.5	3.00 76.2	1.00 25.4	1.13 28.7	.38 9.7
2.00 50.8	1/2 x 13	1.75 44.5	-	1.00 25.4	1.13 28.7	.38 9.7
2.50 63.5	1/2 x 13	1.75 44.5	3.00 76.2	1.50 38.1	1.50 38.1	.56 14.2
2.50 63.5	5/8 x 11	1.75 44.5	-	1.50 38.1	1.50 38.1	.56 14.2

**Specification**

- Stainless steel **NI**  
European Standard No. 1.4305 (AISI 303)
- Steel, blackened finish **ST**
- Machined from solid bar
- Knurled head for non-slip grip
- Stud drilled and pinned into knurled knob body
- RoHS compliant

**Information**

KRSK knurled screws are used for applications which require higher durability than plastic or aluminum, yet appearance is essential.

see also...

- *Knurled Nuts KRSK (with Tapped or Plain Bore)*

**On request**

- Special stud lengths and stud variations

How to order	
<b>1</b>	Handle diameter $d_1$
<b>2</b>	Thread $d_2$
<b>3</b>	Length $l$
<b>4</b>	Material

**1**
**2**
**3**
**4**

**KRSK-1.50-5/16X18-3.00-NI**