



Datasheet for part number FRCIR020R18-1PF80T108

|   |
|---|
| Our Catalog Part Number: FRCIR020R-18-1P-F80-T108   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|  |  |
|--|--|
| Product Datasheet                                  |  |
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Front Panel Mount Receptacle, with rear thread   |
| Mounting   | Flange with through mounting hole  |
| Environmental Class                                | no endbell   |
| Shell Size   | 18   |
| Contact Arrangement                                | 18-1   |
| Total Number of contacts                           | 10 contacts  |
| Number of Contacts Size 16                         | 10 contacts size 16  |
| Gender   | Pin  |
| Contact Type                                       | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating                                    | Gold   |
| Shell Material                                     | Aluminium alloy  |
| Shell Plating                                      | Zinc/Cobalt black trivalent passivation (conductive)   |
| Wire Size Cross Section for Contacts Size 16       | 1,0-1,5 mm <sup>2</sup> or AWG 18-16   |
| Contact Rating for Contacts Size 16                | Maximum Current = 22 A<br>Rated and Test Current = 13 A<br>Potential Drop max. 74 mV   |
| Shock Resistance                                   | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                              | differs by position of contact - consult factory or refer to catalog   |
| Operating Voltage DC                               | differs by position of contact - consult factory or refer to catalog   |
| Operating Voltage AC                               | differs by position of contact - consult factory or refer to catalog   |
| Dielectric strength - Minimum Flashover AC RMS     | differs by position of contact - consult factory or refer to catalog   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot) | differs by position of contact - consult factory or refer to catalog   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |