


Heat Shrink End Caps

- Applications include insulating and protecting wires and cables
- Adhesive lined inner wall seals and provides excellent protection against moisture
- Voltage rating of 600 V
- Shrink ratio: 2.5:1 (HSEC); 3:1 (HSECFR)

- Temperature range: -40°F to 257°F (-40°C to 125°C) HSEC
-67°F to 239°F (-55°C to 110°C) HSECFR
- For wet locations
- Material: Adhesive lined black cross-linked Polyolefin; HSECFR = Flame retardant



HSEC



HSECFR



| Part Number | Min. Expanded I.D. | | Max. Recovered I.D. | | Nominal Recovered Wall Thickness | | Cap Length | | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|--------------------|------|---------------------|------|----------------------------------|-----|------------|-------|----------------|----------------|
| | In. | mm | In. | mm. | In. | mm | In. | mm | | |
| HSEC0.5-X | 0.47 | 11.9 | 0.18 | 4.6 | 0.09 | 2.2 | 1.5 | 37.6 | 10 | 100 |
| HSEC0.8-X | 0.79 | 20.1 | 0.30 | 7.6 | 0.10 | 2.4 | 1.8 | 45.5 | 10 | 100 |
| HSEC1.0-X | 1.15 | 29.2 | 0.45 | 11.4 | 0.11 | 2.8 | 2.8 | 71.1 | 10 | 100 |
| HSEC1.5-5 | 1.58 | 40.1 | 0.68 | 17.3 | 0.14 | 3.6 | 3.2 | 82.0 | 5 | 50 |
| HSEC2.0-5 | 2.25 | 57.2 | 0.98 | 24.9 | 0.15 | 3.8 | 4.3 | 109.0 | 5 | 50 |
| HSEC4.0-2 | 3.92 | 99.6 | 1.78 | 45.2 | 0.15 | 3.8 | 5.4 | 136.4 | 2 | 10 |

Heat Shrink End Caps – Flame Retardant

| | | | | | | | | | | |
|--------------|------|------|------|------|------|-----|-----|------|----|-----|
| HSECFR0.5-XY | 0.51 | 13.0 | 0.16 | 4.1 | 0.09 | 2.3 | 2.5 | 63.5 | 10 | 100 |
| HSECFR0.8-XY | 0.75 | 19.1 | 0.24 | 6.1 | 0.09 | 2.3 | 2.5 | 63.5 | 10 | 100 |
| HSECFR1.0-XY | 1.10 | 27.9 | 0.35 | 8.9 | 0.12 | 3.0 | 3.0 | 76.2 | 10 | 100 |
| HSECFR1.5-5Y | 1.50 | 38.1 | 0.47 | 11.9 | 0.16 | 4.1 | 3.5 | 88.9 | 5 | 50 |
| HSECFR2.0-5Y | 2.00 | 50.8 | 0.63 | 16.0 | 0.16 | 4.1 | 3.5 | 88.9 | 5 | 50 |

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index