ت م			0	₿ >	•	7	
			LAYOUT SHOWN AS EXAM	PLE			
	Keying Shown as example						
CHARACTERISTICS	Connector dimension	1					
-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 29.4 Max						
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z 31 Max VV THREAD M18x1-6g]	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List			
-Durability : 500 Mating cycles			FR Not Listed PN: 8D513W03SA				
-Delivered with Souriau contacts and Accessories			FIN. 0D313700	55A			
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 18-10-201	6 First Release				
_		ISS DATE	Latest modification - by		MOD N°	_	
		Designed By:	Date:	CUSTOMER DRAWING		_	
		TITLE	TITLE Aluminium Plug 8D series				
BASIC SERIES: 8D 5 - 13 W 03 SHELL TYPE : Plug with RFI Shielding - 13 W 03	S A	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		_	
CONTACT TYPE : Standard Crimp Contact	ORIEI		WWW.SOURIAU.COM	This document is the p SOURIAU it must not be reproc			
SHELL SIZE : 13	CONTACT TYPE : SOCKET(5			communicated without	permission		
	CONTACT LAY	OUT : 13-03 FORMAT	SOURIAU D	RG N°	SHEET		
PLATING : W = Olive drab Cadmium		A3	8D513W03		1/2		

r	I		G	п	т	D		C	
		Contact Layout	:						
		03							
4)						
		3#16							
	Ctc A B	13-03 X 2.39 0	Y 1.47 -2.79						
ى	С	-2.39	1.47						
	L								
								due to a use the Specifications	not be liable for a of the Products w issued by either onal recommend
N						L			Coun
								Р	N: 8D513
						A	18 10 2016	First Release	
								Latest modificatio	n - by
						Desig	gned By:	Date:	
							TITLE		Alumi
_ _							CALE -	$\bigcirc \bigcirc$	General linear Tolerances: ±
							DURIAU	WWW	SOURIAU.
						FO	RMAT		SOURIAL

G

Н

F

Е

A3

D

С

