




## MULTILAYER CERAMIC CHIP CAPACITORS



### **CGA Series Open Mode Capacitors**

Type: CGA4 [EIA CC0805]

Issue date: January 2013

**TDK MLCC  
Global Catalog**

Version A13

## REMINDERS

Please read before using this product

### SAFETY REMINDERS


#### REMINDERS

1. If you intend to use a product listed in this catalog for a purpose that may cause loss of life or other damage, you must contact our company's sales window.
2. We may modify products or discontinue production of a product listed in this catalog without prior notification.
3. We provide "Delivery Specification" that explain precautions for the specifications and safety of each product listed in this catalog. We strongly recommend that you exchange these delivery specifications with customers that use one of these products.
4. If you plan to export a product listed in this catalog, keep in mind that it may be a restricted item according to the "Foreign Exchange and Foreign Trade Control Law". In such cases, it is necessary to acquire export permission in harmony with this law.
5. Any reproduction or transferring of the contents of this catalog is prohibited without prior permission from our company.
6. We are not responsible for problems that occur related to the intellectual property rights or other rights of our company or a third party when you use a product listed in this catalog. We do not grant license of these rights.
7. This catalog only applies to products purchased through our company or one of our company's official agencies. This catalog does not apply to products that are purchased through other third parties.

Notice : Effective January 2013, TDK will use a new catalog part number which adds product thickness and packaging specification detail. This new part number should be referenced on all catalog orders going forward, and is not applicable for OEM part number orders. Please be aware the last five digits of the TDK catalog part number will differ from the TDK item description (internal control number) on the product label. Contact your local TDK Sales representative for more information.

(Example)

Catalog Issued date	TDK Part Number (In Catalog)	TDK Item Description (On Delivery Label)
Prior to January 2013	C1608C0G1E103J	C1608C0G1E103JT000N
January 2013 and Later	C1608C0G1E103J080AA	C1608C0G1E103JT000N



# CGA Series


## Open Mode Capacitor

Type: CGA4 [EIA CC0805]

### Features



- Increase resistance to mechanical bending, temperature cycle, vibration, and electrical stresses.
- When a chip capacitor is cracked by mechanical stress such as board bending, open mode construction helps user reduce the risk of short circuits.
- The Open Mode design defines that the L-Gap length shall be wider than the terminal band width
- AEC Q-200 Automotive qualified.



- The Open Mode concept does not guaranteed MLCC will always fail open. This design is intended to reduce the risk of the MLCC failing short. All MLCC caution guidelines apply.

### Applications



- Automotive and other high stress applications
- Battery line circuits with high board flex stress
- DC-DC Converter

### Shape & Dimensions



L	Body Length
W	Body Width
T	Body Height
B	Terminal Width
G	Terminal Spacing



### Part Number Construction

CGA • 4 • J • 2 • X7R • 1H • 104 • K • 125 • A • M

### Series Name

### Dimensions L x W (mm)

Case Code	Length	Width	Terminal
4	2.00 ± 0.20	1.25 ± 0.20	0.20 min.

### Thickness T Code (mm)

Thickness Code	Thickness
F	0.85 mm
J	1.25 mm

### Voltage Condition for Life Test

Code	Condition
2	2 × R.V.

### Temperature Characteristics

Temperature Characteristics	Capacitance Change	Temperature Range
X7R	± 15%	-55 to +125°C
X8R	± 15%	-55 to +150°C

### Rated Voltage (DC)

Voltage Code	Voltage (DC)
1H	50V

### Nominal Capacitance (pF)

The capacitance is expressed in three digit codes and in units of pico Farads (pF). The first and second digits identify the first and second significant figures of the capacitance. The third digit identifies the multiplier. R designates a decimal point.  
 Ex. 0R2 = 0.2pF; 103 = 10,000pF; 105 = 1,000,000pF = 1,000nF = 1μF

### Capacitance Tolerance

Tolerance Code	Tolerance
K	± 10%

### Nominal Thickness

Thickness Code	Thickness
085	0.85 mm
125	1.25 mm

### Packaging Style

Packaging Code	Style
A	178mm Reel / 4mm Pitch

### Special Reserved Code

Code	Description
M	Open Mode Design



## Capacitance Range Chart

## CGA4(2012) [EIA CC0805]

## Capacitance Range Chart

 Temperature Characteristics: X7R ( $\pm 15\%$ ), X8R ( $\pm 15\%$ )  
 Rated Voltage: 50V (1H)

Capacitance (pF)	Cap Code	Tolerance	X7R	X8R
			1H (50V)	1H (50V)
22,000	223	K: $\pm 10\%$		
33,000	333			
47,000	473			
68,000	683			
100,000	104			

## Standard Thickness

- 0.85 mm
- 1.25 mm



## Capacitance Range Table

## Class 2 (Temperature Stable)

 Temperature Characteristics: X7R (-55 to +125°C,  $\pm 15\%$ )

Capacitance	Case Size	Thickness (mm)	Capacitance Tolerance	TDK Part Number
				Rated Voltage Edc: 50V
100 nF	2012	1.25 +0.25/-0.20	$\pm 10\%$	CGA4J2X7R1H104K125AM

## Class 2 (Temperature Stable)

 Temperature Characteristics: X8R (-55 to +150°C,  $\pm 15\%$ )

Capacitance	Case Size	Thickness (mm)	Capacitance Tolerance	TDK Part Number
				Rated Voltage Edc: 50V
22 nF	2012	0.85 $\pm$ 0.15	$\pm 10\%$	CGA4F2X8R1H223K085AM
33 nF	2012	0.85 $\pm$ 0.15	$\pm 10\%$	CGA4F2X8R1H333K085AM
47 nF	2012	1.25 $\pm$ 0.20	$\pm 10\%$	CGA4J2X8R1H473K125AM
68 nF	2012	1.25 $\pm$ 0.20	$\pm 10\%$	CGA4J2X8R1H683K125AM