

Special function module - EEM-2DIO-MA600 - 2901371

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Special functional module with two digital inputs and outputs for EEM-MA600



Your advantages

- ✓ Two digital inputs and outputs
- ✓ Configurable threshold values



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356585019

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	22.5 mm
Height	65 mm
Depth	48 mm

Ambient conditions

Ambient temperature (operation)	-10 °C ... 55 °C (14 °F to 131 °F)
Ambient temperature (storage/transport)	-20 °C ... 85 °C (-4 °F ... 185 °F)
Max. permissible relative humidity (operation)	≤ 95 %
Max. salt spray content	≤ 2.5 %

Input data

Description of the input	Optocoupler input
--------------------------	-------------------

Special function module - EEM-2DIO-MA600 - 2901371

Technical data

Input data

Number	2
Voltage input signal	10 V DC ... 30 V DC
Input pulse length	10 ms
Peak offstate voltage	30 V DC

Output data

Output description	Relay output
Number	2
Maximum switching voltage	250 V AC/DC
Switching capacity	1150 VA (5 A / 230 V AC)
Electrical service life	1 x 10 ⁶ (Switching cycles with ohmic load)

Interfaces

Connection method	Pluggable screw terminal block
-------------------	--------------------------------

General

Supply voltage	9 V (via EEM-MA600)
Color	black
Conformance	CE-compliant
Test voltage	3.5 kV AC (50 Hz, 1 min.)

Standards and Regulations

Conformance	CE-compliant
UL, USA/Canada	UL 61010-1
	CSA-C22.2 No. 61010-1
	cULus

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Listed / cUL Listed / EAC / cULus Listed


Ex Approvals

Approval details

Special function module - EEM-2DIO-MA600 - 2901371

Approvals

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 357804
-----------	---	---	---------------

cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 357804
------------	---	---	---------------

EAC			RU *- DE.A*30.B.01628
-----	---	--	--------------------------

cULus Listed			
--------------	---	--	--

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>