Г	Ξ	G	н <b>т</b>	r	п		0	Φ		
4		Z	ØS							4
cى			~~~ <del>~</del>				LAYOUT SHOWN	AS EXAMPLE		3
	CHARACTERISTICS -Standard : Based on MI	L-DTL-38999 Series III	Keying Sh	own as example Connector o Dim dc	Nominal					
	-Shell Plating -Insulator -Contacts -Seals & Grommet	: Aluminium : Black Zinc Nickel : Thermoplastic : Copper Alloy : Silicon Elastomer		ØS Z VV THREAD	25 Max 31 Max M15x1-6g		Ca	ts which does not comply wher of the Parties or by a the parties or by a the production, technical notice.)	with Iird party	2
	-Durability -Delivered with Souriau	: Gold over copper Alloy 0.8μm min : 500 Mating cycles contacts and Accessories · -65°C to +175°C	nimum					11Z02SN		
	-Salt Spray	: 500 hours : 17.15 g ± 10%				A 18-10-2016 ISS DATE Designed By:	<ul> <li>First Release</li> <li>Latest modification - by</li> <li>Date:</li> </ul>	CUS	MOD N STOMER DRAWING	<u>N°</u>
	BASIC SERIES:	8D 5 -	11 Z 02 S N	N		SCALE	Alu General lin Tolerance		NPRDS / PROJECT	
-	SHELL TYPE : Plug with CONTACT TYPE : Stand SHELL SIZE : 11			CONTACT	ORIENTATION : N TYPE : SOCKET(500 Matings)	NA SOURIAU		U.COM	859 This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
	PLATING : Z = B	ack Zinc Nickel			CONTACT LAYOUT : 11-02	FORMAT A3		AU DRG N° 1Z02SN-C	SHEET 1/2	

r	<b>工</b>	G	н <b>г</b>	m		0
		Contact Layout				
4	.x. (2)	+Y IB IA IB IA -Y .095 .41mm) .095				
	Cont posit ID A B Shell size 11 -2	tion X-axis Y-axis (mm) (mm) +.095 (2.41) +.000 (.00)				
ω						
	-				[	
						SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommenda
N						Count FR
						PN: 8D511
						116 First Release
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumi
<b>_</b>					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT	SOURIAL
l		<u> </u>	F	r i	A3	8D511Z
	Н	G		E	D	C

