			0		A	7
4						4
ω			LAYOUT SHOWN AS EX	ZAMPLE		3
	Keying Shown as example					
CHARA	ACTERISTICS Connector dimension					
-Standa	ard : Based on MIL-DTL-38999 Series III ØS 35.7 Max					
-Shell Pl -Insulato -Contac -Seals &	Shell Material A luminium Z 31 Max SOURIAU shall not be liable for any non-conformity or damage -Shell Plating : Black Zinc Nickel VV THREAD M25x1-6g due to a use of the Products which does not comply with -Insulator : Thermoplastic the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) -Contacts : Silicon Elastomer Silicon Elastomer					
-Durabil	ct Plating : Gold over copper Alloy 0.8μm minimum ility : 500 Mating cycles red with Souriau contacts and Accessories	FR Not Listed PN: 8D517Z08SA			2	
-Tempe	erature Range -65°C to +175°C	A 18-10-2016	First Palazca			_
-Salt Spi	bray : 500 hours					
-Mass	: 37.62 g ± 10%	ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAV	MOD N°	+
		TITLE Aluminium Plug 8D series				
BASIC SI	SERIES: 8D 5 - 17 Z 08 S A TYPE : Plug with RFI Shielding	SCALE -	General linear Tolerances:	NPRDS / PROJE 859	CT	-
	CT TYPE : Standard Crimp Contact ORIENTATION : A	SOURIAU	WWW.SOURIAU.CO	OM SOU it must not be	s the property of RIAU reproduced or	
	SIZE : 17 CONTACT TYPE : SOCKET(500 Matings)	FORMAT			vithout permission	_
PLATING	G : Z = Black Zinc Nickel CONTACT LAYOUT : 17-08	FORMAT A3	SOURIAU		SHEET	
	H G F E	D A5	8D517Z0	BSA-C	1/2	

_	Ŧ	۵	п –	m		0
		Contact Layout				
4	-x ($ \begin{array}{c} $				
	Cont positio A B C C D C D E F F	Contacts (Insert arrangement 17-8) act X-axis Y-axis (mm) + 0.00 (0.00) + 236 (5.99) + 128 (3.25) + 086 (2.18) + 230 (5.84) - 078 (1.98) + 0.94 (2.39) - 216 (5.49) - 0.94 (2.39) - 216 (5.49)				
ယ	G H Sheli Arrangement Nu	128 (3.25) +.086 (2.18)				
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o
N						(professional recommenda Count FR PN: 8D517
					ISS DATE Designed By:	16 First Release Latest modification - by Date:
-					SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	U WWW.SOURIAU. SOURIAU 8D517Z
L	Н	G	F	E	D	C

