D D			0	₿ >	
	ØS-				
			LAYOUT SHOWN AS EXA	AMPLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimen	nsion			
-Standard : Based on MIL-DTL-38999 Series III	Dim N	Nominal			
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Z	9.4 Max 31 Max 118x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm mi	inimum		Country FR	Jurisdiction & Control List Not Listed	
-Contact Plating . Gold over copper Alloy 0.8µmm -Durability : 500 Mating cycles	mmum		PN: 8D513W08SB		
-Delivered with Souriau contacts and Accessories			FIN: 8031344	UOJD	
-Temperature Range65°C to +175°C		A 19-1	10-2016 First Release		
-Salt Spray       : 500 hours         -Mass       : 26.6 g ± 10%			DATE Latest modification - by		MOD N°
		Designed By:		CUSTOMER DRAWING	
		TITL	E Aluminit	um Plug 8D series	
	13 W 08 S B	SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
SHELL TYPE : Plug with RFI Shielding		NA		This document is the prop	erty of
CONTACT TYPE       : Standard Crimp Contact       ORIENTATION : B         SHELL SIZE : 13       CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM it must not be reprodu		
				communicated without per	mission
SHELL SIZE : 13					
SHELL SIZE : 13 PLATING : W = Olive drab Cadmium		DNTACT LAYOUT : 13-08	SOURIAU I 8D513W0		SHEET 1/2

r	Ŧ	G	г П	m		0
		Contact Layout				
4		$x \begin{pmatrix} g \\ g$				
		Contacts           (Insert arrangement 13-8)           Intact (BD)         Contact location           X-axis (mm)         Y-axis (mm)           A         +.065 (1.65)         +.157 (3.99)           B         +.170 (4.32)         +.000 (0.00)           C         +.120 (3.05)        120 (3.05)           D        000 (0.00)        170 (4.32)           E        120 (3.05)        120 (3.05)           F        170 (4.32)         +.000 (0.00)           G        065 (1.65)         +.157 (3.99)           H         +.0000 (0.00)         +.044 (1.12)				
ω	Shell Arrangement Nu size no. c 13 -8	imber of Size Service Contact Supersede ontacts contacts rating location 8 20 I All MS20051-				
	F					SOURIAU shall not be liable for an due to a use of the Products wi the Specifications issued by either o (professional recommenda
N						PN: 8D513
					A 19-10-20 ISS DATE Designed By:	116 First Release
					SCALE	Alumin General linear
<u> </u>					NA	Tolerances:
					SOURIA	
					FORMAT A3	SOURIAU 8D513W
	Н	G	F F	E \	D	C

