



NOTE 1 This dimension indicates the condition after assembling to a cable.  
 2. When this plug is mated with receptacle, clamping torque of part No. 2  
 should be 1.5 to 3 N·m.  
 Optional plastic spanner below can be used as a substitution.

Plastic spanner	Part No.	Code No.
	MF10-T1	CL709-0205-8-00

3 Ferrules are not included in this product.  
 Please use an optional simplex simplified MU ferrule.

7	BRASS	CHROME PLATING	14	ZIRCONIA	
6	NBR RUBBER	COLOR:BLACK	13	NYLON	
5	NBR RUBBER	COLOR:BLACK	12	STAINLESS STEEL	NYELOCK
4	PBT	COLOR:BLACK	11	ALUMINIUM ALLOY	ANODIC OXIDE COATING
3	ALUMINIUM ALLOY	ANODIC OXIDE COATING	10	STAINLESS STEEL	
2	BRASS	CHROME PLATING	9	PPS RESIN	COLOR:BLACK
1	ZINC DIECAST	CHROME PLATING	8	NBR RUBBER	COLOR:BLACK
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS

UNITS	SCALE	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
mm	2 : 1	1				
HIROSE ELECTRIC CO., LTD.			APPROVED : MT. SHIBUTANI 18.03.28 CHECKED : MT. SHIBUTANI 18.03.28 DESIGNED : SI. MATSUMOTO 18.03.28 DRAWN : SR. TOYOKAWA 18.03.28	DRAWING NO. EDC-176258-31-00 PART NO. MF10S-WP6C02-0200(31) CODE NO. CL709-0525-9-31		