

VIEW ON MATING SIDE

∞	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B
◁	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A = 32 STANDARD CONTACTS L=3

B = 32 STANDARD CONTACTS L=3

S = 64 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G1/O = Contact area level / Termination fin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85001-0001 sht.1
Technical Data	PS-85003-0001

B	G1/O
A	G1/O
Contact symbol	Perform. level
	Contact position number

C	see ECN No. 2204	96/07/18 Cd	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
	LTR			

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2° INCH METRIC	DRWG BY	SIGN	REVISE ONLY ON CAD SYSTEM	SH. REV.
	CHK'D BY	SIGN		
	3 PLACE ± .	Ca		
2 PLACE ± .	KN			
1 PLACE ± .	APP'D BY	SCALE		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				
DESIGN DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.			
EQUIVALENT DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.			
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY				

CAD/CAM PROJECT NAME	S8500102	THIS DRAWING CONTAINS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
	s51	
TITLE	64 pos. Male connector acc. DIN 41612 style B contacts arrangement	
MOLEX®	MOLEX EUROPE	SHEET NO. DATE 1 OF 1 95/05/22
PART NO.	85001-0256	DWG NO. SDA-85001-0256
		SIZE A